

🕳 Order

Now



LP3907

ZHCSEA3U-JUNE 2007-REVISED JANUARY 2018

LP3907 双路1 A 和600 mA 降压转换器和双路300 mA LDO 具有 I2C 接口

Technical

Documents

1 特性

- 输入电压范围: 2.8V 至 5.5V
- 兼容高级 应用 处理器和现场可编程门阵列 (FPGA)
- 2 个低压降线性稳压器 (LDO),用于为内部处理器的运行和 I/O 供电
- 高速串行接口用于对器件功能和设置进行独立控制
- 精密的内部基准电压
- 热过载保护
- 电流过载保护
- 软件可编程稳压器
- 针对 Buck1 和 Buck2 的外部上电复位功能(带延迟功能的电源正常指示)
- 配有欠压闭锁检测器,用于监视输入电源电压
 - 降压直流/直流转换器(降压)
 - 可编程 Vour:
 - Buck1: 1A 时为 0.8V 至 2V
 - Buck2: 600mA 时为 1V 至 3.5V
 - 效率高达 96%
 - 2.1MHz 脉冲宽度调制 (PWM) 开关频率
 - 低负载条件下
 从 PWM 模式自动切换到脉冲频率调制 (PFM)
 模式
 - **±3%** 的输出电压精度
 - 自动软启动
- 线性稳压器 (LDO)
 - 可编程 V_{OUT} 1V 至 3.5V
 (JJ11、FX6W 和 JX6X 选项除外)
 - 300mA 输出电流
 - 30mV (典型值) 压降
 - 使用 LP3907 并借助 WEBENCH[®] 电源设计器 创建定制设计方案
- 2 应用
- 现场可编程门阵列 (FPGA),数字信号处理器 (DSP)内核电源
- 应用 处理器
- 外设 I/O 电源
- 助听器
- 电子测量装置
- 备用电池供电型设备

3 说明

🥭 Tools &

Software

LP3907 器件是专为低功耗 FPGA、微处理器和 DSP 优化的多功能、可编程电源管理单元 (PMU)。该器件 集成了两个具有动态电压调节 (DVS) 功能的高效 1A、 600mA 降压直流/直流转换器、两个 300mA 线性稳压 器和一个 400kHz I²C 接口,使主机控制器可以访问该 器件的内部控制寄存器。LP3907 还 具有 可编程的加 电序列。

Support &

Community

22

具备诸多功能,其中包括可编程的加电序列、通信控制 (l2C)、动态电压调节、过流保护、电源正常指示、同步整流、热关断以及欠压锁定。对于 需要 轻负载的应用,此款高效同步开关降压稳压器可进入 PFM 模式,以较低的开关频率和电源电流运行,从而在极轻负载下保持高效率。

器件信息(1)

| 田川日心 | | | | |
|---------|------------|-----------------|--|--|
| 器件型号 | 封装 | 封装尺寸(标称值) | | |
| 1 02007 | WQFN (24) | 4.00mm x 4.00mm | | |
| LP3907 | DSBGA (25) | 2.49mm × 2.49mm | | |

(1) 如需了解所有可用封装,请参阅数据表末尾的可订购产品附 录。



Copyright © 2016, Texas Instruments Incorporated

典型应用电路





目录

| 1 | 特性1 |
|---|--|
| 2 | 应用1 |
| 3 | 说明1 |
| 4 | 修订历史记录 2 |
| 5 | 器件比较 台式机 |
| 6 | Pin Configuration and Functions |
| 7 | Specifications |
| | 7.1 Absolute Maximum Ratings |
| | 7.2 ESD Ratings |
| | 7.3 Recommended Operating Conditions (Bucks) |
| | 7.4 Thermal Information |
| | 7.5 General Electrical Characteristics |
| | 7.6 Low Dropout Regulators, LDO1 And LDO2 10 |
| | 7.7 Buck Converters SW1, SW2 |
| | 7.8 I/O Electrical Characteristics 11 |
| | 7.9 Power-On Reset (POR) Threshold/Function 11 |
| | 7.10 I ² C Interface Timing Requirements 11 |
| | 7.11 Typical Characteristics — LDO 12 |
| | 7.12 Typical Characteristics — Bucks 14 |
| | 7.13 Typical Characteristics — Buck1 15 |
| | 7.14 Typical Characteristics — Buck2 16 |
| | 7.15 Typical Characteristics — Bucks 17 |
| 8 | Detailed Description 19 |
| | 8.1 Overview 19 |
| | |

| | 8.2 | Functional Block Diagram | 19 |
|----|------|--|----|
| | 8.3 | Feature Description | 20 |
| | 8.4 | Device Functional Modes | 28 |
| | 8.5 | Programming | 29 |
| | 8.6 | Register Maps | 32 |
| 9 | Appl | ication and Implementation | 42 |
| | 9.1 | Application Information | 42 |
| | 9.2 | Typical Application | 42 |
| 10 | Pow | er Supply Recommendations | 48 |
| | 10.1 | Analog Power Signal Routing | 48 |
| 11 | Layo | out | 49 |
| | 11.1 | DSBGA Layout Guidelines | 49 |
| | 11.2 | Layout Example | 50 |
| | 11.3 | Thermal Considerations of WQFN Package | 50 |
| 12 | 器件 | 和文档支持 | 51 |
| | 12.1 | 器件支持 | 51 |
| | 12.2 | 文档支持 | 51 |
| | 12.3 | 商标 | 51 |
| | 12.4 | 接收文档更新通知 | 51 |
| | 12.5 | 社区资源 | 51 |
| | 12.6 | 静电放电警告 | 51 |
| | 12.7 | Glossary | 51 |
| 13 | 机械 | 、封装和可订购信息 | 52 |
| | | | |

4 修订历史记录

注: 之前版本的页码可能与当前版本有所不同。

| Changes from Revision T (November 2016) to Revision U | Page |
|---|-------|
| 已添加 Webench 链接 已删除 删除已过时的 OPN 表 3 | 1 |
| Changes from Revision S (April 2016) to Revision T | Page |
| • 己更改 更改了改进的 SEO 的数据表标题,将动态电压"管理"更改为"调节",向"说明"中添加了新段落 | 1 |
| Changes from Revision R (May 2015) to Revision S | Page |
| • 已添加 将附加条目添加至 应用 | 1 |
| Changed symbol "θn" to "e_N" in Low Dropout Regulators, LDO1 And LDO2 Electrical Char table | 10 |
| Changes from Revision Q (January 2015) to Revision R | Page |
| Added last sentence to "NOTE" | |
| Changes from Revision P (November 2014) to Revision Q | Page |
| 已更改将更新的附加值更改至新的默认器件选项 | 4 |
| Changed Handling Ratings table to ESD Ratings table; update Thermal Information | |



Changes from Revision O (May 2013) to Revision P

已添加器件信息表和处理额定值表,特性描述,器件功能模式,应用和实施,电源相关建议,布局,器件和文档支持以及机械、封装和可订购信息部分;已将一些曲线移至应用曲线部分。.....1

3

TEXAS INSTRUMENTS

www.ti.com.cn

5 器件比较 台式机

表 1. 默认 I²C 地址

| 封装类型 | 默认 I ² C 地址 |
|-------------|------------------------|
| 24 引线 WQFN | 60 |
| 25 凸点 DSBGA | 61 |

表 2. 电源块

| 中派曲谷) | 电源块i | 运行 | 〉→ 4 2 | |
|----------|---------------------|--------|----------------------------------|--|
| 电源埃າ和八 | 启用 禁用 | | 1工作 | |
| VINLDO12 | VIN+ ⁽¹⁾ | VIN+ | 始终供电 | |
| AVDD | VIN+ | VIN+ | 始终供电 | |
| VIN1 | VIN+ | VIN+ | | |
| VIN2 | VIN+ | VIN+ | | |
| LDO1 | ≤ VIN+ | ≤ VIN+ | 如果启用,V _{IN} 最小值为 1.74V | |
| LDO2 | ≤ VIN+ | ≤ VIN+ | 如果启用, V _{IN} 最小值为 1.74V | |

(1) VIN+ 是设备支持的最大电压。



LP3907 ZHCSEA3U – JUNE 2007 – REVISED JANUARY 2018

www.ti.com.cn

表 3. 默认器件选项

| 部件号(1)(2) | BUCK1 | BUCK2 | LDO1 | LDO2 | 降压模式 | 默认 EN_T 延迟 | 默认 UVLO |
|---------------------|-------|-------|----------------------|----------------------|--------|------------|---------|
| LP3907SQ-TJXIP/NOPB | 1.2V | 3.3V | 1.8V | 2.5V | 强制 PWM | 001 | 启用 |
| LP3907SQ-JXQX/NOPB | 1.2V | 3.3V | 2.6V | 3.3V | 自动模式 | 010 | 启用 |
| LP3907SQ-PJXIX/NOPB | 1.2V | 3.3V | 1.8V | 3.3V | 强制 PWM | 010 | 启用 |
| LP3907SQ-PFX6W/NOPB | 1V | 3.3V | 2.65V ⁽³⁾ | 3.2V | 强制 PWM | 010 | 启用 |
| LP3907SQ-BJXQX/NOPB | 1.2V | 3.3V | 2.6V | 3.3V | 强制 PWM | 010 | 禁用 |
| LP3907TL-JJ11/NOPB | 1.2V | 1.8V | 2.85V ⁽³⁾ | 2.85V ⁽³⁾ | 自动模式 | 010 | 启用 |
| LP3907TLX-JJ11/NOPB | 1.2V | 1.8V | 2.85V ⁽³⁾ | 2.85V ⁽³⁾ | 自动模式 | 010 | 启用 |
| LP3907TL-JSXS/NOPB | 1.2V | 2.8V | 3.3V | 2.8V | 自动模式 | 010 | 启用 |
| LP3907TL-JJCP/NOPB | 1.2V | 1.8V | 1.2V | 2.5V | 自动模式 | 010 | 启用 |
| LP3907TL-PLNTO/NOPB | 1.3V | 2.2V | 2.9V | 2.4V | 强制 PWM | 010 | 启用 |

(1) 要获得最新的封装和订购信息,请参见本文档末尾的封装选项附录,或者浏览 TI 网站 www.ti.com.cn。
(2) 封装图样、散热数据和符号可从网站 www.ti.com/packaging 中获取。
(3) 电压为固定值,不可编程。



6 Pin Configuration and Functions





| Pin Functions | | | | | | |
|----------------|-----------------|----------|-----|---------------------|--|--|
| | PIN | | | | | |
| WQFN NUMBER | DSBGA NUMBER | NAME | I/O | TYPE ⁽¹⁾ | DESCRIPTION | |
| 1 | B4, B5 | VINLDO12 | I | PWR | Analog power for internal functions (VREF, BIAS, I ² C, Logic) | |
| 2 | C4 | EN_T | I | D | Enable for preset power on sequence. (See .) | |
| 3 | C3 | nPOR | 0 | D | nPOR power on reset pin for both Buck1 and Buck 2. Open drain logic output 100 -k Ω pullup resistor. nPOR is pulled to ground when the voltages on these supplies are not good. See <i>Flexible Power-On Reset (Power Good with Delay)</i> section for more info. | |
| 4 | C5 | GND_SW1 | G | G | Buck1 NMOS Power Ground | |
| 5 | D5 | SW1 | 0 | PWR | Buck1 switcher output pin | |
| 6 | E5 | VIN1 | I | PWR | Power in from either DC source or battery to Buck1 | |
| 7 | D4 | ENSW1 | I | D | Enable pin for Buck1 switcher, a logic HIGH enables Buck1 | |
| 8 | E4 | FB1 | I | А | Buck1 input feedback terminal | |
| 9 | D3 | GND_C | G | G | Non switching core ground pin | |
| 10 | E3 | AVDD | I | PWR | Analog power for Buck converters | |
| 11 | E2 | FB2 | I | А | Buck2 input feedback terminal | |
| 12 | D2 | ENSW2 | I | D | Enable pin for Buck2 switcher, a logic HIGH enables Buck2 | |
| 13 | E1 | VIN2 | I | PWR | Power in from either DC source or Battery to Buck2 | |
| 14 | D1 | SW2 | 0 | PWR | Buck2 switcher output pin | |
| 15 | C1 | GND_SW2 | G | G | Buck2 NMOS power ground | |
| 16 | C2 | SDA | I/O | D | I ² C cata (bidirectional) | |
| 17 | B2 | SCL | I | D | l ² C clock | |
| 18 | B1 | GND_L | G | G | LDO ground | |
| 19 | A1 | VINLDO1 | I | PWR | Power in from either DC source or battery to input terminal to LDO1 | |
| 20 | A2 | LDO1 | 0 | PWR | LDO1 output | |
| 21 | B3 | ENLDO1 | I | D | LDO1 enable pin, a logic HIGH enables the LDO1 | |
| 22 | A3 | ENLDO2 | I | D | LDO2 enable pin, a logic HIGH enables the LDO2 | |
| 23 | A4 | LDO2 | 0 | PWR | LDO2 output | |
| 24 | A5 | VINLDO2 | I | PWR | Power in from either DC source or battery to input terminal to LDO2. | |
| DAP | | DAP | GND | GND | Connection is not necessary for electrical performance, but it is recommended for better thermal dissipation. | |

(1) A: Analog Pin I

D: Digital Pin **G:** Ground Pin

PWR: Power Pin

I: Input Pin

I/O: Input/Output Pin O: Output Pin.

7 Specifications

7.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) (1)(2)

| | MIN | MAX | UNIT |
|---|------|------|------|
| V _{IN} , SDA, SCL | -0.3 | 6 | V |
| GND to GND SLUG | | ±0.3 | V |
| Power dissipation (WQFN (RTW))(P_{D_MAX}) ($T_A = 85^{\circ}C$, $T_{MAX} = 125^{\circ}C$) ⁽³⁾ | | 1.43 | W |
| Power dissipation (DSBGA (YZR)) ⁽³⁾ (P_{D_MAX}) ($T_A = 85^{\circ}C$, $T_{MAX} = 125^{\circ}C$) | | 0.78 | W |
| Junction temperature, T _{J-MAX} | | 150 | °C |
| Maximum lead temperature (soldering) | | 260 | °C |
| Storage temperature, T _{stg} | -65 | 150 | °C |

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions (Bucks). Exposure to absolute-emaximum-rated conditions for extended periods may affect device reliability.

(2) All voltages are with respect to the potential at the GND pin.

(3) In applications where high power dissipation and/or poor package thermal resistance is present, the maximum ambient temperature may have to be derated. Maximum ambient temperature (T_{A-MAX}) is dependent on the maximum operating junction temperature (T_{J-MAX-OP} = 125°C), the maximum power dissipation of the device in the application (P_{D-MAX}), and the junction-to-ambient thermal resistance of the part/package in the application (R_{θJA}), as given by the following equation: T_{A-MAX} = T_{J-MAX-OP} - (R_{θJA} × P_{D-MAX}).

7.2 ESD Ratings

| | | | VALUE | UNIT |
|--------------------|-------------------------|---|-------|------|
| | | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾ | ±2000 | |
| V _(ESD) | Electrostatic discharge | Charged-device model (CDM), per JEDEC specification JESD22-C101 $^{\left(2\right) }$ | ±750 | V |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

7.3 Recommended Operating Conditions (Bucks)

over operating free-air temperature range (unless otherwise noted)⁽¹⁾⁽²⁾⁽³⁾⁽⁴⁾

| | MIN | MAX | UNIT |
|--|-----|---------------------------|------|
| V _{IN} | 2.8 | 5.5 | V |
| V _{EN} | 0 | (V _{IN} + 0.3 V) | V |
| Junction temperature, T _J | -40 | 125 | °C |
| Ambient temperature, T _A ⁽⁵⁾ | -40 | 85 | °C |

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltages are with respect to the potential at the GND pin.

(3) Minimum (Minimum) and Maximum (Maximum) limits are ensured by design, test, or statistical analysis. Typical numbers are not ensured, but do represent the most likely norm.

(4) Buck $V_{IN} \ge V_{OUT} + 1 V$.

(5) Junction-to-ambient thermal resistance is highly application and board-layout dependent. In applications where high maximum power dissipation exists, special care must be paid to thermal dissipation issues in board design.



7.4 Thermal Information

See⁽¹⁾⁽²⁾⁽³⁾

| | | LP3 | | |
|-----------------------|--|---------|---------|------|
| | THERMAL METRIC ⁽⁴⁾ | RTW | YZR | UNIT |
| | | 24 PINS | 25 PINS | |
| $R_{\theta JA}$ | Junction-to-ambient thermal resistance | 32.7 | 58.7 | °C/W |
| R _{0JC(top)} | Junction-to-case (top) thermal resistance | 31.2 | 0.3 | °C/W |
| $R_{\theta J B}$ | Junction-to-board thermal resistance | 11.2 | 8.0 | °C/W |
| ΨJT | Junction-to-top characterization parameter | 0.2 | 0.6 | °C/W |
| Ψјв | Junction-to-board characterization parameter | 11.2 | 8.0 | °C/W |
| R _{0JC(bot)} | Junction-to-case (bottom) thermal resistance | 1.4 | N/A | °C/W |

Junction-to-ambient thermal resistance is highly application and board-layout dependent. In applications where high maximum power (1) dissipation exists, special care must be paid to thermal dissipation issues in board design.

Internal thermal shutdown circuitry protects the device from permanent damage. Thermal shutdown engages at T_J = 160°C (typical) and (2)disengages at T_J = 140°C (typical).

In applications where high power dissipation and/or poor package thermal resistance is present, the maximum ambient temperature may (3) have to be derated. Maximum ambient temperature (T_{A-MAX}) is dependent on the maximum operating junction temperature (T_{J-MAX-OP} = 125°C), the maximum power dissipation of the device in the application (P_{D-MAX}), and the junction-to-ambient thermal resistance of the part/package in the application ($R_{\theta,JA}$), as given by the following equation: $T_{A-MAX} = T_{J-MAX-OP} - (R_{\theta,JA} \times P_{D-MAX})$. For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application

(4) report.

7.5 **General Electrical Characteristics**

Unless otherwise noted, V_{IN} = 3.6 V and T_J = 25°C.⁽¹⁾⁽²⁾⁽³⁾⁽⁴⁾

| | PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|------------------|-----------------------------|---|-----|-----|-----|------|
| l _Q | VINLDO12 shutdown current | $V_{IN} = 3.6 V$ | | 3 | | μA |
| V _{POR} | Power-on reset threshold | V _{DD} falling edge ⁽⁴⁾ | | 1.9 | | V |
| T _{SD} | Thermal shutdown threshold | | | 160 | | °C |
| T _{SDH} | Thermal shutdown hysteresis | | | 20 | | °C |
| UVLO | Undervoltage lockout | Rising | | 2.9 | | V |
| | | Falling | | 2.7 | | v |

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

All voltages are with respect to the potential at the GND pin. (2)

This specification is ensured by design. (3)

(4) VPOR is voltage at which the EPROM resets. This is different from the UVLO on VINLDO12, which is the voltage at which the regulators shut off, and is also different from the nPOR function, which signals if the regulators are in a specified range.

RUMENTS

7.6 Low Dropout Regulators, LDO1 And LDO2

Unless otherwise noted, $V_{IN} = 3.6 \text{ V}$, $C_{IN} = 1 \mu\text{F}$, $C_{OUT} = 0.47 \mu\text{F}$, and $T_{II} = 25^{\circ}\text{C}$.⁽¹⁾⁽²⁾⁽³⁾⁽⁴⁾⁽⁵⁾⁽⁶⁾⁽⁷⁾

| | PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|---|---|--|---------------------|------|----------------------|-------|
| V _{IN} | Operational voltage range | VINLDO1 and VINLDO2 PMOS pins ⁽⁸⁾ | 1.74 ⁽⁹⁾ | | 5.5 ⁽⁹⁾ | V |
| V _{OUT} Accuracy | Output voltage accuracy (default V _{OUT}) | Load current = 1 mA | -3% ⁽⁹⁾ | | 3% ⁽⁹⁾ | |
| A)/ | Line regulation | $V_{IN} = (V_{OUT} + 0.3 V)$ to 5 V, ⁽⁷⁾ , load current = 1 mA | | | 0.15 ⁽⁹⁾ | %/V |
| ΔVOUT | Load regulation | $V_{IN} = 3.6 \text{ V},$ Load current = 1 mA to I_{MAX} | | | 0.011 ⁽⁹⁾ | %/mA |
| I _{SC} | Short circuit current limit | LDO1-2, $V_{OUT} = 0 V$ | | 500 | | mA |
| $V_{\text{IN}} - V_{\text{OUT}}$ | Dropout voltage | Load current = 50 mA | | 30 | 200 ⁽⁹⁾ | mV |
| PSRR | Power supply ripple rejection | f = 10 kHz, load current = I _{MAX} | | 45 | | dB |
| e _N | Supply output noise | 10 Hz < F < 100 KHz | | 80 | | μVrms |
| | Quiescent current on | I _{OUT} = 0 mA | | 40 | | μA |
| I _Q ⁽⁶⁾ (10) | Quiescent current on | I _{OUT} = I _{MAX} | | 60 | | μA |
| | Quiescent current off | EN is de-asserted ⁽¹¹⁾ | | 0.03 | | μA |
| T _{ON} | Turnon time | Start-up from shutdown | | 300 | | μs |
| $V_{IN} - V_{OUT}$ PSRR e_{N} $I_{Q}^{(6) (10)}$ T_{ON} C_{OUT} | | Capacitance for stability $0^{\circ}C \le T_{J} \le 125^{\circ}C$ | 0.33 ⁽⁹⁾ | 0.47 | | μF |
| | Output capacitor | $-40^{\circ}C \le T_{J} \le 125^{\circ}C$ | 0.68 | 1 | | μF |
| | | ESR | 5 ⁽⁹⁾ | | 500 ⁽⁹⁾ | mΩ |

(1) All voltages are with respect to the potential at the GND pin.

(2) Minimum (MIN) and maximum (MAX) limits are ensured by design, test, or statistical analysis. Typical numbers are not ensured, but do represent the most likely norm.

(3) CIN, COUT: Low-ESR Surface-Mount Ceramic Capacitors (MLCCs) used in setting electrical characteristics.

(4) The device maintains a stable, regulated output voltage without a load.

- (5) Dropout voltage is the voltage difference between the input and the output at which the output voltage drops to 100 mV below its nominal value.
- (6) Quiescent current is defined here as the difference in current between the input voltage source and the load at V_{OUT}.

(7) V_{IN} minimum for line regulation values is 1.8 V.

(8) Pins 24, 19 can operate from V_{IN} min of 1.74 V to a V_{IN} max of 5.5 V. This rating is only for the series pass PMOS power FET. It allows the system design to use a lower voltage rating if the input voltage comes from a buck output.

(9) Limits apply over the entire junction temperature range for operation, -40° C to $+125^{\circ}$ C.

(10) The I_Q can be defined as the standing current of the LP3907 when the I²C bus is active and all other power blocks have been disabled with the I²C bus, or it can be defined as the I²C bus active, and the other power blocks are active under no load condition. These two values can be used by the system designer when the LP3907 is powered using a battery.

(11) The I_Q exhibits a higher current draw when the EN pin is de-asserted because the I^2C buffer pins draw an additional 2 μ A.

7.7 Buck Converters SW1, SW2

Unless otherwise noted, $V_{IN} = 3.6 \text{ V}$, $C_{IN} = 10 \ \mu\text{F}$, $C_{OUT} = 10 \ \mu\text{F}$, $L_{OUT} = 2.2 \ \mu\text{H}$ ceramic, and $T_J = 25^{\circ}\text{C}$.⁽¹⁾⁽²⁾⁽³⁾⁽⁴⁾⁽⁵⁾⁽⁶⁾

| | PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-------------------|-------------------------------|---|--------------------|--------|-------------------|------|
| V _{FB} | Feedback voltage | | -3% ⁽⁷⁾ | | 3% ⁽⁷⁾ | |
| V _{OUT} | Line regulation | 2.8 V < V _{IN} < 5.5 V I _{OUT} = 10 mA | | 0.089 | | %/V |
| | Load regulation | 100 mA < I _{OUT} < I _{MAX} | | 0.0013 | | %/mA |
| Eff | Efficiency | Load current = 250 mA | | 96% | | |
| I _{SHDN} | Shutdown supply current | EN is de-asserted | | 0.01 | | μA |
| fosc | Internal oscillator frequency | | 1.7 ⁽⁷⁾ | 2.1 | | MHz |

(1) All voltages are with respect to the potential at the GND pin.

(2) Minimum (Min) and Maximum (Max) limits are ensured by design, test, or statistical analysis. Typical numbers are not ensured, but do represent the most likely norm.

(3) C_{IN}, C_{OUT}: Low-ESR Surface-Mount Ceramic Capacitors (MLCCs) used in setting electrical characteristics.

(4) The device maintains a stable, regulated output voltage without a load.

(5) Quiescent current is defined here as the difference in current between the input voltage source and the load at V_{OUT}.

(6) Buck $V_{IN} \ge V_{OUT} + 1 V$.

(7) Limits apply over the entire junction temperature range for operation, -40°C to +125°C.



Buck Converters SW1, SW2 (continued)

Unless otherwise noted, $V_{IN} = 3.6$ V, $C_{IN} = 10$ μ F, $C_{OUT} = 10$ μ F, $L_{OUT} = 2.2$ - μ H ceramic, and $T_J = 25^{\circ}C$.⁽¹⁾⁽²⁾⁽³⁾⁽⁴⁾⁽⁵⁾⁽⁶⁾

| | PARAMETER | TEST CONDITIONS | MIN TY | P MAX | UNIT |
|-------------------------------|------------------------------------|---------------------------|--------|-------|------|
| I _{PEAK} | Buck1 peak switching current limit | | 1 | 5 | А |
| | Buck2 peak switching current limit | | | 1 | |
| I _Q ⁽⁸⁾ | Quiescent current "on" | No load PFM mode | 3 | 3 | μA |
| R _{DSON} (P) | Pin-pin resistance PFET | | 20 | 0 | mΩ |
| R _{DSON} (N) | Pin-pin resistance NFET | | 18 | 0 | mΩ |
| T _{ON} | Turnon time | Start up from shutdown | 50 | 0 | μs |
| C _{IN} | Input capacitor | Capacitance for stability | 10 | | μF |
| C _{OUT} | Output capacitor | Capacitance for stability | 10 | | μF |

(8) The I_Q can be defined as the standing current of the LP3907 when the I²C bus is active and all other power blocks have been disabled with the I²C bus, or it can be defined as the I²C bus active, and the other power blocks are active under no load condition. These two values can be used by the system designer when the device is powered using a battery.

7.8 I/O Electrical Characteristics

Unless otherwise noted: Limits apply over the entire junction temperature range for operation, $T_J = -40^{\circ}$ C to $+125^{\circ}$ C.⁽¹⁾

| | PARAMETER | TEST CONDITIONS | MIN MAX | UNIT |
|-----------------|------------------|-----------------|---------|------|
| V _{IL} | Input low level | | 0.4 | V |
| V _{IH} | Input high level | | 1.2 | v |

(1) This specification is ensured by design.

7.9 Power-On Reset (POR) Threshold/Function

| | PARAMETER | TEST CONDITIONS | MIN TY | P MAX | UNIT |
|-----------|---|--|--------|--------|------|
| nPOR | nPOR = Power on reset forBuck1 and Buck2 | Default | 5 |) | ms |
| nPOR | Percentage of target voltage Buck1 | V _{BUCK1} AND V _{BUCK2} rising | 94% | / 0 | |
| threshold | or Buck2 | V _{BUCK1} OR V _{BUCK2} falling | 85% | / 0 | |
| VOL | Output level low | Load = IoL = 500 mA | 0.2 | 3 0.5 | V |

7.10 I²C Interface Timing Requirements

Unless otherwise noted, V_{IN} = 3.6 V and T_J = 25°C.⁽¹⁾

| | | | MIN | NOM | MAX | UNIT |
|----------------------|--|-------|-----|-----|-----|------|
| fclk | Clock frequency | | | | 400 | kHz |
| t _{BF} | Bus-free time between start and stop | | 1.3 | | | μs |
| t _{HOLD} | Hold time repeated start condition | | 0.6 | | | μs |
| t _{CLKLP} | CLK low period | | 1.3 | | | μs |
| t _{CLKHP} | CLK high period | | 0.6 | | | μs |
| t _{SU} | Set-up time repeated start condition | - (1) | 0.6 | | | μs |
| t _{DATAHLD} | Data hold time | See | 0 | | | μs |
| t _{DATASU} | Data set-up time | | 100 | | | ns |
| T _{SU} | Set-up time for start condition | | 0.6 | | | μs |
| T _{TRANS} | Maximum pulse width of spikes that must be suppressed by the input filter of both DATA & CLK signals | | | 50 | | ns |

(1) This specification is ensured by design.

TEXAS INSTRUMENTS

www.ti.com.cn

7.11 Typical Characteristics — LDO

 $T_A = 25^{\circ}C$ unless otherwise noted.





Typical Characteristics — LDO (continued)

 $T_A = 25^{\circ}C$ unless otherwise noted.



TEXAS INSTRUMENTS

www.ti.com.cn

7.12 Typical Characteristics — Bucks

 $V_{\rm IN}\!\!=2.8$ V to 5.5 V, $T_{\rm A}=25^{\circ}C$





7.13 Typical Characteristics — Buck1

 $V_{\text{IN}}\text{=}$ 2.8 V to 5.5 V, T_{A} = 25°C, V_{OUT} = 1.2 V, 2 V





7.14 Typical Characteristics — Buck2

 $V_{\text{IN}}\text{=}$ 4.5 V to 5.5 V, T_{A} = 25°C, V_{OUT} = 1.8 V, 3.3 V





7.15 Typical Characteristics — Bucks

 V_{IN} = 3.6 V, T_A = 25°C, V_{OUT} = 1.2 V unless otherwise noted.





Typical Characteristics — Bucks (continued)

 $V_{\text{IN}}\text{=}$ 3.6 V, T_{A} = 25°C, V_{OUT} = 1.2 V unless otherwise noted.





8 Detailed Description

8.1 Overview

The LP3907 supplies the various power needs of the application by means of two linear low drop regulators (LDO1 and LDO2) and two buck converters (SW1 and SW2). Table 4 lists the output characteristics of the various regulators.

| | | | OUTPUT | |
|-----------------------|---------|----------------------------|-----------------|---|
| SUPPLY ⁽¹⁾ | LOAD | V _{OUT} RANGE (V) | RESOLUTION (mV) | I _{MAX} MAXIMUM OUTPUT CURRENT (mA) |
| LDO1 | analog | 1 to 3.5 | 100 | 300 |
| LDO2 | analog | 1 to 3.5 | 100 | 300 |
| SW1 | digital | 0.8 to 2 | 50 | 1000 |
| SW2 | digital | 1 to 3.5 | 100 | 600 |

(1) For default values of the regulators, consult $\frac{1}{5}$ 3.

8.2 Functional Block Diagram



Copyright © 2016, Texas Instruments Incorporated

TEXAS INSTRUMENTS

8.3 Feature Description

8.3.1 DC-DC Converters

8.3.1.1 Linear Low Dropout Regulators (LDOs)

LDO1 and LDO2 are identical linear regulators targeting analog loads characterized by low noise requirements. LDO1 and LDO2 are enabled through the ENLDO pin or through the corresponding LDO1 or LDO2 control register. The output voltages of both LDOs are register programmable. The default output voltages are factory programmed during final test, which can be tailored to the specific needs of the system designer.



Copyright © 2016, Texas Instruments Incorporated

Figure 30. LDO Block Diagram

8.3.1.2 No-Load Stability

The LDOs remain stable and in regulation with no external load. This is an important consideration in some circuits, for example, CMOS RAM keep-alive applications.

8.3.1.3 LDO and LDO2 Control Registers

LDO1 and LDO2 can be configured by means of the LDO1 and LDO2 control registers. The output voltage is programmable in steps of 100 mV from 1 V to 3.5 V by programming bits D4-D0 in the LDO Control registers. Both LDO1 and LDO2 are enabled by applying a logic 1 to the ENLDO1 and ENLDO2 pin. Enable/disable control is also provided through enable bit of the LDO1 and LDO2 control registers. The value of the enable LDO bit in the register is logic 1 by default. The output voltage can be altered while the LDO is enabled.

8.3.2 SW1, SW2: Synchronous Step-Down Magnetic DC-DC Converters

8.3.2.1 Functional Description

The LP3907 incorporates two high-efficiency synchronous switching buck regulators, SW1 and SW2, that deliver a constant voltage from a single Li-Ion battery to the portable system processors. Using a voltage mode architecture with synchronous rectification, both bucks have the ability to deliver up to 1000 mA and 600 mA, respectively, depending on the input voltage and output voltage (voltage headroom), and the inductor chosen (maximum current capability).

There are three modes of operation depending on the current required: PWM, PFM, and shutdown. PWM mode handles current loads of approximately 70 mA or higher, delivering voltage precision of $\pm 3\%$ with 90% efficiency or better. Lighter output current loads cause the device to automatically switch into PFM for reduced current consumption ($I_Q = 15 \mu A$ typical) and a longer battery life. The standby operating mode turns off the device, offering the lowest current consumption. PWM or PFM mode is selected automatically or PWM mode can be forced through the setting of the buck control register.

Both SW1 and SW2 can operate up to a 100% duty cycle (PMOS switch always on) for low drop out control of the output voltage. In this way the output voltage is controlled down to the lowest possible input voltage.

Additional features include soft-start, undervoltage lockout, current overload protection, and thermal overload protection.



Feature Description (continued)

8.3.2.2 Circuit Operation Description

A buck converter contains a control block, a switching PFET connected between input and output, a synchronous rectifying NFET connected between the output and ground (BCKGND pin) and a feedback path. During the first portion of each switching cycle, the control block turns on the internal PFET switch. This allows current to flow from the input through the inductor to the output filter capacitor and load. The inductor limits the current to a ramp with a slope of

$$\frac{V_{IN} - V_{OUT}}{L}$$
(1)

by storing energy in a magnetic field. During the second portion of each cycle, the control block turns the PFET switch off, blocking current flow from the input, and then turns the NFET synchronous rectifier on. The inductor draws current from ground through the NFET to the output filter capacitor and load, which ramps the inductor current down with a slope of

The output filter stores charge when the inductor current is high, and releases it when low, smoothing the voltage across the load.

8.3.2.3 PWM Operation

During PWM operation the converter operates as a voltage-mode controller with input voltage feed forward. This allows the converter to achieve excellent load and line regulation. The DC gain of the power stage is proportional to the input voltage. To eliminate this dependence, feed forward voltage inversely proportional to the input voltage is introduced.

8.3.2.4 Internal Synchronous Rectification

While in PWM mode, the buck uses an internal NFET as a synchronous rectifier to reduce rectifier forward voltage drop and associated power loss. Synchronous rectification provides a significant improvement in efficiency whenever the output voltage is relatively low compared to the voltage drop across an ordinary rectifier diode.

8.3.2.5 Current Limiting

A current limit feature allows the converter to protect itself and external components during overload conditions. PWM mode implements current limiting using an internal comparator that trips at 1.5 A for Buck1 and at 1 A for Buck2 (typical). If the output is shorted to ground the device enters a timed current limit mode where the NFET is turned on for a longer duration until the inductor current falls below a low threshold, ensuring inductor current has more time to decay, thereby preventing runaway.

8.3.2.6 PFM Operation

At very light loads, the converter enters PFM mode and operates with reduced switching frequency and supply current to maintain high efficiency.

The part automatically transitions into PFM mode when either of two conditions occurs for a duration of 32 or more clock cycles:

- A. The inductor current becomes discontinuous, or
- B. The peak PMOS switch current drops below the I_{MODE} level

(Typically
$$I_{MODE} < 66 \text{ mA} + \frac{V_{IN}}{160\Omega}$$
)

(3)

(2)



Feature Description (continued)

During PFM operation, the converter positions the output voltage slightly higher than the nominal output voltage during PWM operation, allowing additional headroom for voltage drop during a load transient from light to heavy load. The PFM comparators sense the output voltage with the feedback pin and control the switching of the output FETs such that the output voltage ramps between 0.8% and 1.6% (typical) above the nominal PWM output voltage. If the output voltage is below the *low* PFM comparator threshold, the PMOS power switch is turned on. It remains on until the output voltage exceeds the 'high' PFM threshold or the peak current exceeds the I_{PFM} level set for PFM mode. The typical peak current in PFM mode is:

$$I_{PFM} = 66 \text{ mA} + \frac{V_{\text{IN}}}{80\Omega}$$
(4)

Once the PMOS power switch is turned off, the NMOS power switch is turned on until the inductor current ramps to zero. When the NMOS zero-current condition is detected, the NMOS power switch is turned off. If the output voltage is below the *high* PFM comparator threshold (see Figure 31), the PMOS switch is again turned on and the cycle is repeated until the output reaches the desired level. Once the output reaches the *high* PFM threshold, the NMOS switch is turned on briefly to ramp the inductor current to zero and then both output switches are turned off and the part enters an extremely low power mode. Quiescent supply current during this *sleep* mode is less than 30 μ A, which allows the part to achieve high efficiencies under extremely light load conditions. When the output drops below the *low* PFM threshold, the cycle repeats to restore the output voltage to approximately 1.6% above the nominal PWM output voltage.

If the load current increases during PFM mode (see Figure 31) causing the output voltage to fall below the 'low2' PFM threshold, the part automatically transitions into fixed-frequency PWM mode.

8.3.2.7 SW1, SW2 Operation

SW1 and SW2 have selectable output voltages ranging from 0.8 V to 3.5 V (typical). Both SW1 and SW2 in the LP3907 are I²C register controlled and are enabled by default through the internal state machine of the device following a power-on event that moves the operating mode to the Active state. (See *Flexible Power Sequencing of Multiple Power Supplies*.) The SW1 and SW2 output voltages revert to default values when the power-on sequence has been completed. The default output voltage for each buck converter is factory programmable. (See *Application and Implementation*.)

8.3.2.8 SW1, SW2 Control Registers

SW1, SW2 can be enabled/disabled through the corresponding control register.

The Modulation mode PWM/PFM is by default automatic and depends on the load as described above in the functional description. The modulation mode can be overridden by setting I²C bit to a logic 1 in the corresponding buck control register, forcing the buck to operate in PWM mode regardless of the load condition.



Figure 31. Operation in PFM Mode and Transfer to PWM Mode



Feature Description (continued)

8.3.2.9 Soft Start

The soft-start feature allows the power converter to gradually reach the initial steady state operating point, thus reducing start-up stresses and surges. The two LP3907 buck converters have a soft-start circuit that limits inrush current during start-up. During start-up the switch current limit is increased in steps. Soft start is activated only if EN goes from logic low to logic high after V_{IN} reaches 2.8V. Soft start is implemented by increasing switch current limit in steps of 180 mA, 300 mA, and 720 mA for Buck1; 161 mA, 300 mA, and 536 mA for Buck2 (typical switch current limit). The start-up time thereby depends on the output capacitor and load current demanded at start-up.

8.3.2.10 Low Dropout Operation

The LP3907 can operate at 100% duty cycle (no switching; PMOS switch completely on) for low dropout support of the output voltage. In this way the output voltage is controlled down to the lowest possible input voltage. When the device operates near 100% duty cycle, output voltage ripple is approximately 25 mV. The minimum input voltage needed to support the output voltage is:

$$V_{IN, MIN} = I_{LOAD} \times (R_{DSON, PFET} + R_{INDUCTOR}) + V_{OUT}$$

where

- I_{LOAD} = Load current
- R_{DSON, PFET} = Drain to source resistance of PFET switch in the triode region
- R_{INDUCTOR} = Inductor resistance

8.3.2.11 Flexible Power Sequencing of Multiple Power Supplies

The LP3907 provides several options for power on sequencing. The two bucks can be individually controlled with ENSW1 and ENSW2. The two LDOs can also be individually controlled with ENLDO1 and ENLDO2.

If the user desires a set power on sequence, the chip is programmable through I²C and raise EN_T from LOW to HIGH to activate the power on sequencing.

8.3.2.12 Power-Up Sequencing Using the EN_T Function

EN_T assertion causes the LP3907 to emerge from Standby mode to Full Operation mode at a preset timing sequence. By default, the enables for the LDOs and Bucks (ENLDO1, ENLDO2, EN_T, ENSW1, ENSW2) are 500 K Ω internally pulled down, which causes the part to stay OFF until enabled. If the user wishes to use the preset timing sequence to power on the regulators, transition the EN_T pin from Low to High. Otherwise, simply tie the enables of each specific regulator HIGH to turn on automatically.

EN_T is edge triggered with rising edge signaling the chip to power on. The EN_T input is deglitched, and the default is set at 1 ms. As shown in Figure 32 and Figure 33, a rising EN_T edge starts a power-on sequence, while a falling EN_T edge starts a shutdown sequence. If EN_T is high, toggling the external enables of the regulators has no effect on the chip.

The regulators can also be programmed through I²C to turn on and off. By default, I²C enables for the regulators turned ON.

The regulators are on following the pattern below:

Regulators on = $(I^2C \text{ enable})$ AND (External pin enable OR EN_T high).

NOTE

The EN_T power-up sequencing may also be employed immediately after V_{IN} is applied to the device. However, V_{IN} must be stable for approximately 8 ms minimum before EN_T be asserted high to ensure internal bias, reference, and the Flexible POR timing are stabilized. This initial EN_T delay is necessary only upon first time device power on for power sequencing function to operate properly. If the device is powered, the EN_T logic must be stable for 12 ms minimum before switching state.

(5)

Feature Description (continued)



Figure 32. Power Rail Enable Logic



Figure 33. LP3907 Default Power-Up Sequence

| | DESCRIPTION | MIN | NOM | TYP | UNIT |
|----------------|---|-----|-----|-----|------|
| t ₁ | Programmable delay from EN_T assertion to V _{CC} _Buck1 On | | 1.5 | | ms |
| t ₂ | Programmable delay from EN_T assertion to V _{CC} _Buck2 On | | 2 | | ms |
| t ₃ | Programmable delay from EN_T assertion to V _{CC} _LDO1 On | | 3 | | ms |
| t ₄ | Programmable delay from EN_T assertion to V _{CC} _LDO2 On | | 6 | | ms |







Table 6. Power-Off Timing Specification

| | DESCRIPTION | MIN NOM | MAX | UNIT |
|----------------|---|---------|-----|------|
| t ₁ | Programmable delay from EN_T deassertion to V_{CC} _Buck1 Off | 1.5 | | ms |
| t ₂ | Programmable delay from EN_T deassertion to V_{CC} _Buck2 Off | 2 | | ms |
| t ₃ | Programmable delay from EN_T deassertion to V_{CC} _LDO1 Off | 3 | | ms |
| t ₄ | Programmable delay from EN_T deassertion to V_{CC} _LDO2 Off | 6 | | ms |

8.3.3 Flexible Power-On Reset (Power Good with Delay)

The LP3907 is equipped with an internal power-on-reset (POR) circuit which monitors the output voltage levels on Bucks 1 and 2. The nPOR is an open drain logic output which is logic LOW when either of the buck outputs are below 91% of the rising value, or when one or both outputs fall below 82% of the desired value. The time delay between output voltage level and nPOR is enabled is (50 μ s, 50 ms, 100 ms, 200 ms) 50 ms by default. The system designer can choose the external pullup resistor (that is, 100 k Ω) for the nPOR pin.





Texas Instruments

www.ti.com.cn

Figure 35 shows the simplest application of the POR, where both switcher enables are tied together. In Case 1, EN1 causes nPOR to transition LOW and triggers the nPOR delay counter. If the power supply for Buck2 does not come on within that period, nPOR stays LOW, indicating a power fail mode. Case 2 indicates the vice versa scenario if Buck1 supply did not come on. In both cases the nPOR remains LOW.

Case 3 shows a typical application of the POR, where both switcher enables are tied together. Even if RDY1 ramps up slightly faster than RDY2 (or vice versa), then nPOR signal triggers a programmable delay before going HIGH, as explained below.



Figure 36. Faults Occurring in Counter Delay After Start-Up

Figure 36 details the power good with delay with respect to the enable signals EN1, and EN2. The RDY1, RDY2 are internal signals derived from the output of two comparators. Each comparator has been trimmed as follows:

| COMPARATOR LEVEL | BUCK SUPPLY LEVEL |
|------------------|-------------------|
| HIGH | Greater than 94% |
| LOW | Less than 85% |

The circuits for EN1 and RDY1 is symmetrical to EN2 and RDY2, so each reference to EN1 and RDY1 also works for EN2 and RDY2 and vice versa.

If EN1 and RDY1 signals are High at time t1, then the RDY1 signal rising edge triggers the programmable delay counter (50 μ s, 50 ms, 100 ms, 200 ms). This delay forces nPOR LOW between time interval t1 and t2. nPOR is then pulled high after the programmable delay is completed. Now if EN2 and RDY2 are initiated during this interval the nPOR signal ignores this event.

If either RDY1or RDY2 were to go LOW at t3 then the programmable delay is triggered again.



LP3907 ZHCSEA3U – JUNE 2007 – REVISED JANUARY 2018

www.ti.com.cn



Figure 37. nPOR Mask Window

If the EN1 and RDY1 are initiated in normal operation, then nPOR is asserted and deasserted as explained in Figure 37.

Case 1 shows the case where EN2 and RDY2 are initiated after triggered programmable delay. To prevent the nPOR being asserted again, a masked window (5 ms) counter delay is triggered off the EN2 rising edge. nPOR is still held HIGH for the duration of the mask, whereupon the nPOR status afterwards depends on the status of both RDY1 and RDY2 lines.

Case 2 shows the case where EN2 is initiated after the RDY1 triggered programmable delay, but RDY2 never goes HIGH (Buck2 never turns on). Normal operation operation of nPOR occurs wilth respect to EN1 and RDY1, and the nPOR signal is held HIGH for the duration of the mask window. We see that nPOR goes LOW after the masking window has timed out because it is now dependent on RDY1 and RDY2, where RDY2 is LOW.

TEXAS INSTRUMENTS

www.ti.com.cn



Figure 38. Design Implementation of the Flexible Power-On Reset

An internal power-on reset of the device is used with EN1, and EN2 to produce a reset signal (LOW) to the delay timer nPOR. EN1 and RDY1 or EN2 and RDY2 are used to generate the set signal (HIGH) to the delay timer. S = R = 1 never occurs. The mask timers are triggered off EN1 and EN2 which are gated with RDY1, and RDY2 to generate outputs to the final AND gate to generate the nPOR.

8.3.4 Undervoltage Lockout

The LP3907 features an undervoltage lockout circuit. The function of this circuit is to continuously monitor the raw input supply voltage (VINLDO12) and automatically disables the four voltage regulators whenever this supply voltage is less than 2.8 VDC.

The circuit incorporates a bandgap based circuit that establishes the reference used to determine the 2.8 VDC trip point for a V_{IN} OK – Not OK detector. This V_{IN} OK signal is then used to gate the enable signals to the four regulators of the device. When VINLDO12 is greater than 2.8 VDC the four enables control the four regulators, when VINLDO12 is less than 2.8 VDC the four regulators are disabled by the V_{IN} detector being in the "Not OK" state. The circuit has built-in hysteresis to prevent chattering occurring.

8.4 Device Functional Modes

8.4.1 Shutdown Mode

During shutdown the PFET switch, reference, control and bias circuitry of the converters are turned off. The NFET switch is on in shutdown to discharge the output. When the converter is enabled, soft start is activated. It is recommended to disable the converter during the system power up and undervoltage conditions when the supply is less than 2.8 V.



8.5 Programming

8.5.1 I²C-Compatible Serial Interface

8.5.1.1 PC Signals

The LP3907features an I²C-compatible serial interface, using two dedicated pins: SCL and SDA for I²C clock and data respectively. Both signals need a pullup resistor according to the I²C specification. The LP3907 interface is an I²C slave that is clocked by the incoming SCL clock.

Signal timing specifications are according to the I²C bus specification. The maximum bit rate is 400kbit/s. See I²C specification from NXP Semiconductors for further details.

8.5.1.2 P^C Data Validity

The data on the SDA line must be stable during the HIGH period of the clock signal (SCL); for example, the state of the data line can only be changed when CLK is LOW.



Figure 39. I²C Signals: Data Validity

8.5.1.3 PC Start and Stop Conditions

START and STOP bits classify the beginning and the end of the I²C session. START condition is defined as the SDA signal transitioning from HIGH to LOW while the SCL line is HIGH. STOP condition is defined as the SDA transitioning from LOW to HIGH while the SCL is HIGH. The ²C master always generates START and STOP bits. The I²C bus is considered to be busy after START condition and free after STOP condition. During data transmission, I²C master can generate repeated START conditions. First START and repeated START conditions are equivalent, function-wise.



Figure 40. Start and Stop Conditions

8.5.1.4 Transferring Data

Every byte put on the SDA line must be eight bits long, with the most significant bit (MSB) being transferred first. Each byte of data has to be followed by an acknowledge bit. The acknowledged related clock pulse is generated by the master. The transmitter releases the SDA line (HIGH) during the acknowledge clock pulse. The receiver must pull down the SDA line during the 9th clock pulse, signifying acknowledgment. A receiver which has been addressed must generate an acknowledgment ("ACK") after each byte has been received.

After the START condition, the I²C master sends a chip address. This address is seven bits long followed by an eighth bit which is a data direction bit (R/W).



Programming (continued)

NOTE

According to industry I²C standards for 7-bit addresses, the MSB of an 8-bit address is removed, and communication actually starts with the 7th most significant bit. For the eighth bit (LSB), a "0" indicates a WRITE and a "1" indicates a READ. The second byte selects the register to which the data is written. The third byte contains data to write to the selected register.

The LP3907 has factory-programmed I^2C addresses. The WQFN chip has a chip address of 60'h, while the DSBGA chip has a chip address of 61'h.



Figure 41. I²C Chip Address (see note above)



When a READ function is to be accomplished, a WRITE function must precede the READ function, as shown in the Read Cycle waveform.





Programming (continued)

8.5.2 Factory Programmable Options

Table 7 shows options EPROM programmed during final test of the LP3907. The system designer that needs specific options is advised to contact the TI sales office.

Table 7. Factory-Programmable Options

| FACTORY PROGRAMMABLE OPTIONS | CURRENT VALUE |
|------------------------------|---|
| Enable delay for power on | code 010 (see Control 1 Register (SCR1) 0x07) |
| SW1 ramp speed | 8 mV/µs |
| SW2 ramp speed | 8 mV/µs |

The I²C Chip ID address is offered as a metal mask option. The current address for the WQFN chip equals 0x60, while the address for the DSBGA chip is 0x61.

8.6 Register Maps

8.6.1 LP3907 Control Registers

| REGISTER ADDRESS | REGISTER NAME | READ/WRITE | REGISTER DESCRIPTION |
|---------------------|------------------|------------|---|
| 0x02 | ICRA | R | Interrupt Status Register A |
| 0x07 | SCR1 | R/W | System Control 1 Register |
| 0x10 | BKLDOEN | R/W | Buck and LDO Output Voltage Enable Register |
| 0x11 | BKLDOSR | R | Buck and LDO Output Voltage Status Register |
| 0x20 | VCCR | R/W | Voltage Change Control Register 1 |
| 0x23 | B1TV1 | R/W | Buck1 Target Voltage 1 Register |
| 0x24 | B1TV2 | R/W | Buck1 Target Voltage 2 Register |
| 0x25 | B1RC | R/W | Buck1 Ramp Control |
| 0x29 | B2TV1 | R/W | Buck2 Target Voltage 1 Register |
| 0x2A | B2TV2 | R/W | Buck2 Target Voltage 2 Register |
| 0x2B | B2RC | R/W | Buck2 Ramp Control |
| 0x38 | BFCR | R/W | Buck Function Register |
| 0x39 | LDO1VCR | R/W | LDO1 Voltage Control Registers |
| 0x3A | LDO2VCR | R/W | LDO2 Voltage Control Registers |

8.6.1.1 Interrupt Status Register (ISRA) 0x02

This register informs the System Engineer of the temperature status of the chip.

| | D7-D2 | D1 | D0 |
|--------|----------|--|----------|
| Name | — | Temp 125°C | _ |
| Access | — | R | — |
| Data | Reserved | Status bit for thermal warning PMIC T>125°C 0 – PMIC Temp. < 125°C 1 – PMIC Temp. > 125°C | Reserved |
| Reset | 0 | 0 | 0 |

8.6.1.2 Control 1 Register (SCR1) 0x07

This register allows the user to select the preset delay sequence for power-on timing, to switch between PFM and PWM mode for the bucks, and also to select between an internal and external clock for the bucks.

| | D7 | D6-D4 | D3 | D2 | D1 | D0 |
|--------|----------|--|----------|--|---|----------|
| Name | — | EN_DLY | — | FPWM2 | FPWM1 | ECEN |
| Access | — | R/W | — | R/W | R/W | R/W |
| Data | Reserved | Selects the preset delay sequence from EN_T assertion (shown below) | Reserved | Buck2 PWM /PFM Mode select 0 – Auto Switch PFM - PWM operation 1 – PWM Mode Only | Buck 1 PWM /PFM Mode select 0 – Auto Switch PFM - PWM operation 1 – PWM Mode Only | Reserved |
| Reset | 0 | Factory-Programmed Default | 1 | Factory-Programmed Default | Factory-Programmed Default | 0 |

8.6.1.3 EN_DLY Preset Delay Sequence After EN_T Assertion

| EN_DLY<2:0> | DELAY (ms) | | | | | |
|-------------|------------|-------|------|------|--|--|
| | BUCK1 | BUCK2 | LDO1 | LDO2 | | |
| 000 | 1 | 1 | 1 | 1 | | |
| 001 | 1 | 1.5 | 2 | 2 | | |
| 010 | 1.5 | 2 | 3 | 6 | | |
| 011 | 1.5 | 2 | 1 | 1 | | |
| 100 | 1.5 | 2 | 3 | 6 | | |
| 101 | 1.5 | 1.5 | 2 | 2 | | |
| 110 | 3 | 2 | 1 | 1.5 | | |
| 111 | 2 | 3 | 6 | 11 | | |

8.6.1.4 Buck and LDO Output Voltage Enable Register (BKLDOEN) – 0x10

This register controls the enables for the Bucks and LDOs.

| | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|--------|----------|---------------------------|----------|---------------------------|----------|---------------------------|----------|---------------------------|
| Name | — | LDO2EN | — | LDO1EN | — | BK2EN | — | BK1EN |
| Access | — | R/W | — | R/W | — | R/W | — | R/W |
| Data | Reserved | 0 – Disable 1 – Enable |
| Reset | 0 | 1 | 1 | 1 | 0 | 1 | 0 | 1 |

8.6.1.5 Buck and LDO Status Register (BKLDOSR) – 0x11

This register monitors whether the Bucks and LDOs meet the voltage output specifications.

| | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|--------|--|--|---|---|--------------|---|--------------|---|
| Name | BKS_OK | LDOS_OK | LDO2_OK | LDO1_OK | _ | BK2_OK | _ | BK1_OK |
| Access | R | R | R | R | _ | R | _ | R |
| Data | 0 – Buck 1-2 Not Valid 1 – Bucks Valid | 0 – LDO 1-2 Not Valid 1 – LDOs Valid | 0 – LDO2 Not Valid 1 – LDO2 Valid | 0 – LDO1 Not Valid 1 – LDO1 Valid | Reserve d | 0 – Buck2 Not Valid 1 – Buck2 Valid | Reserve d | 0 – Buck1 Not Valid 1 – Buck1 Valid |
| Reset | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

8.6.1.6 Buck Voltage Change Control Register 1 (VCCR) – 0x20

This register selects and controls the output target voltages for the buck regulators.

| | D7-6 | D5 | D4 | D3-2 | D1 | D0 |
|--------|----------|--|---|----------|--|---|
| Name | _ | B2VS | B2GO | _ | B1VS | B1GO |
| Access | — | R/W | R/W | — | R/W | R/W |
| Data | Reserved | Buck2 Target Voltage Select 0 – B2VT1 1 – B2VT2 | Buck2 Voltage Ramp CTRL 0 – Hold 1 – Ramp to B2VS selection | Reserved | Buck1 Target Voltage Select 0 – B1VT1 1 – B1VT2 | Buck1 Voltage Ramp CTRL 0 – Hold 1 – Ramp to B1VS selection |
| Reset | 00 | 0 | 0 | 00 | 0 | 0 |

LP3907

www.ti.com.cn

8.6.1.7 Buck1 Target Voltage 1 Register (B1TV1) – 0x23

This register allows the user to program the output target voltage of Buck1.

| | D7-D5 | D4 | -D0 | |
|--------|----------|----------------|----------------|--|
| Name | | BK1_VOUT1 | | |
| Access | — | R/W | | |
| Data | Reserved | Buck1 Outpu | ut Voltage (V) | |
| | | 5'h00 | Ext Ctrl | |
| | | 5'h01 | 0.80 | |
| | | 5'h02 | 0.85 | |
| | | 5'h03 | 0.90 | |
| | | 5'h04 | 0.95 | |
| | | 5'h05 | 1.00 | |
| | | 5'h06 | 1.05 | |
| | | 5'h07 | 1.10 | |
| | | 5'h08 | 1.15 | |
| | | 5'h09 | 1.20 | |
| | | 5'h0A | 1.25 | |
| | | 5'h0B | 1.30 | |
| | - | 5'h0C | 1.35 | |
| | | 5'h0D | 1.40 | |
| | | 5'h0E | 1.45 | |
| | - | 5'h0F | 1.50 | |
| | | 5'h10 | 1.55 | |
| | | 5'h11 | 1.60 | |
| | | 5'h12 | 1.65 | |
| | | 5'h13 | 1.70 | |
| | | 5'h14 | 1.75 | |
| | | 5'h15 | 1.80 | |
| | | 5'h16 | 1.85 | |
| | | 5'h17 | 1.90 | |
| | | 5'h18 | 1.95 | |
| | | 5'h19 | 2.00 | |
| | | 5'h1A–5'h1F | 2.00 | |
| Reset | 000 | Factory-Progra | ammed Default | |



8.6.1.8 Buck1 Target Voltage 2 Register (B1TV2) – 0x24

This register allows the user to program the output target voltage of Buck1.

| | D7-D5 | D4- | -D0 | |
|--------|----------|----------------|-------------------------|--|
| Name | — | BK1_VOUT2 | | |
| Access | — | R/ | W | |
| Data | Reserved | Buck1 Outpu | it Voltage (V) | |
| | | 5'h00 | Ext Ctrl ⁽¹⁾ | |
| | | 5'h01 | 0.80 | |
| | | 5'h02 | 0.85 | |
| | | 5'h03 | 0.90 | |
| | | 5'h04 | 0.95 | |
| | | 5'h05 | 1.00 | |
| | | 5'h06 | 1.05 | |
| | | 5'h07 | 1.10 | |
| | | 5'h08 | 1.15 | |
| | | 5'h09 | 1.20 | |
| | | 5'h0A | 1.25 | |
| | | 5'h0B | 1.30 | |
| | | 5'h0C | 1.35 | |
| | | 5'h0D | 1.40 | |
| | | 5'h0E | 1.45 | |
| | | 5'h0F | 1.50 | |
| | | 5'h10 | 1.55 | |
| | | 5'h11 | 1.60 | |
| | | 5'h12 | 1.65 | |
| | | 5'h13 | 1.70 | |
| | | 5'h14 | 1.75 | |
| | | 5'h15 | 1.80 | |
| | | 5'h16 | 1.85 | |
| | | 5'h17 | 1.90 | |
| | | 5'h18 | 1.95 | |
| | | 5'h19 | 2.00 | |
| | | 5'h1A–5'h1F | 2.00 | |
| Reset | 000 | Factory-Progra | ammed Default | |

(1) If using Ext Ctrl, contact TI Sales for support.

8.6.1.9 Buck1 Ramp Control Register (B1RC) - 0x25

This register allows the user to program the rate of change between the target voltages of Buck1.

| | D7 | D6-D4 | D3-D0 | | |
|--------|----------|----------|-------------|-----------------|--|
| Name | | | B1RS | | |
| Access | | | R/ | N | |
| Data | Reserved | Reserved | Data Code | Ramp Rate mV/us | |
| | | | 4h'0 | Instant | |
| | | | 4h'1 | 1 | |
| | | | 4h'2 | 2 | |
| | | | 4h'3 | 3 | |
| | | | 4h'4 | 4 | |
| | | | 4h'5 | 5 | |
| | | | 4h'6 | 6 | |
| | | | 4h'7 | 7 | |
| | | | 4h'8 | 8 | |
| | | | 4h'9 | 9 | |
| | | | 4h'A | 10 | |
| | | | 4h'B - 4h'F | 10 | |
| Reset | 0 | 010 | 100 | 0 | |



8.6.1.10 Buck2 Target Voltage 1 Register (B2TV1) – 0x29

This register allows the user to program the output target voltage of Buck2.

| | D7-D5 | D4 | -D0 |
|--------|----------|---------------|----------------|
| Name | _ | BK2_ | VOUT1 |
| Access | _ | R | /W |
| Data | Reserved | Buck2 Outpu | ut Voltage (V) |
| | | 5'h00 | Ext Ctrl |
| | | 5'h01 | 1.0 |
| | | 5'h02 | 1.1 |
| | | 5'h03 | 1.2 |
| | | 5'h04 | 1.3 |
| | | 5'h05 | 1.4 |
| | | 5'h06 | 1.5 |
| | | 5'h07 | 1.6 |
| | | 5'h08 | 1.7 |
| | | 5'h09 | 1.8 |
| | | 5'h0A | 1.9 |
| | | 5'h0B | 2.0 |
| | | 5'h0C | 2.1 |
| | | 5'h0D | 2.2 |
| | | 5'h0E | 2.4 |
| | | 5'h0F | 2.5 |
| | | 5'h10 | 2.6 |
| | | 5'h11 | 2.7 |
| | | 5'h12 | 2.8 |
| | | 5'h13 | 2.9 |
| | | 5'h14 | 3.0 |
| | | 5'h15 | 3.1 |
| | | 5'h16 | 3.2 |
| | | 5'h17 | 3.3 |
| | | 5'h18 | 3.4 |
| | | 5'h19 | 3.5 |
| | | 5'h1A–5'h1F | 3.5 |
| Reset | 000 | Factory-Progr | ammed Default |

8.6.1.11 Buck2 Target Voltage 2 Register (B2TV2) – 0x2A

This register allows the user to program the output target voltage of Buck2.

| | D7-5 | D4 | -0 | | | |
|--------|----------|--------------------------|-------------------------|--|--|--|
| Name | — | BK2_V | OUT2 | | | |
| Access | — | R/ | N | | | |
| Data | Reserved | Buck2 Output Voltage (V) | | | | |
| | | 5'h00 | Ext Ctrl ⁽¹⁾ | | | |
| | | 5'h01 | 1.0 | | | |
| | | 5'h02 | 1.1 | | | |
| | | 5'h03 | 1.2 | | | |
| | | 5'h04 | 1.3 | | | |
| | | 5'h05 | 1.4 | | | |
| | | 5'h06 | 1.5 | | | |
| | | 5'h07 | 1.6 | | | |
| | | 5'h08 | 1.7 | | | |
| | | 5'h09 | 1.8 | | | |
| | | 5'h0A | 1.9 | | | |
| | | 5'h0B | 2.0 | | | |
| | | 5'h0C | 2.1 | | | |
| | | 5'h0D | 2.2 | | | |
| | | 5'h0E | 2.4 | | | |
| | | 5'h0F | 2.5 | | | |
| | | 5'h10 | 2.6 | | | |
| | | 5'h11 | 2.7 | | | |
| | | 5'h12 | 2.8 | | | |
| | | 5'h13 | 2.9 | | | |
| | | 5'h14 | 3.0 | | | |
| | | 5'h15 | 3.1 | | | |
| | | 5'h16 | 3.2 | | | |
| | | 5'h17 | 3.3 | | | |
| | | 5'h18 | 3.4 | | | |
| | | 5'h19 | 3.5 | | | |
| | | 5'h1A–5'h1F | 3.5 | | | |
| Reset | 000 | Factory-Progra | mmed Default | | | |

(1) If using Ext Ctrl, contact TI Sales for support.



8.6.1.12 Buck2 Ramp Control Register (B2RC) - 0x2B

This register allows the user to program the rate of change between the target voltages of Buck2.

| | D7 | D6-D4 | D | 3-D0 |
|--------|----------|----------|-------------|-----------------|
| Name | | | В | 2RS |
| Access | | | F | R/W |
| Data | Reserved | Reserved | Data Code | Ramp Rate mV/us |
| | | | 4h'0 | Instant |
| | | | 4h'1 | 1 |
| | | | 4h'2 | 2 |
| | | | 4h'3 | 3 |
| | | | 4h'4 | 4 |
| | | | 4h'5 | 5 |
| | | | 4h'6 | 6 |
| | | | 4h'7 | 7 |
| | | | 4h'8 | 8 |
| | | | 4h'9 | 9 |
| | | | 4h'A | 10 |
| | | | 4h'B - 4h'F | 10 |
| Reset | 0 | 010 | 1 | 000 |

8.6.1.13 Buck Function Register (BFCR) – 0x38

This register allows the Buck switcher clock frequency to be spread across a wider range, allowing for less Electro-magnetic Interference (EMI). The spread spectrum modulation frequency refers to the rate at which the frequency ramps up and down, centered at 2 MHz.



Figure 44. Spread Spectrum Modulation Frequency

This register also allows dynamic scaling of the nPOR Delay Timing. The LP3907 is equipped with an internal POR circuit which monitors the output voltage levels on the buck regulators, allowing the user to more actively monitor the power status of the chip.

The UVLO feature continuously monitor the raw input supply voltage (VINLDO12) and automatically disables the four voltage regulators whenever this supply voltage is less than 2.8 VDC. This prevents the user from damaging the power source (such as battery), but can be disabled if the user wishes.

Note that if the supply to VDD_M is close to 2.8 V with a heavy load current on the regulators, the chip is in danger of powering down due to UVLO. If the user wishes to keep the chip active under those conditions, enable the Bypass UVLO feature.

TEXAS INSTRUMENTS

LP3907

ZHCSEA3U – JUNE 2007 – REVISED JANUARY 2018

www.ti.com.cn

| | D7-D5 | D4 | D3-D2 | D1 | D0 |
|--------|----------|---|---|---|---|
| Name | — | BP_UVLO | TPOR | BK_SLOMOD | BK_SSEN |
| Access | — | R/W | R/w | R/W | R/W |
| Data | Reserved | Bypass UVLO monitoring 0 - Allow UVLO 1 - Disable UVLO | nPOR Delay Timing 00 - 50 μs 01 - 50 ms 10 - 100 ms 11 - 200 ms | Buck Spread Spectrum Modulation 0 – 10 kHz triangular wave 1 – 2 kHz triangular wave | Spread Spectrum Function Output 0 – Disabled 1 – Enabled |
| Reset | 000 | Factory-Programmed Default | 01 | 1 | 0 |

8.6.1.14 LDO1 Control Register (LDO1VCR) – 0x39

This register allows the user to program the output target voltage of LDO 1.

For "JJ11" voltage options LDO1 has a fixed output voltage of 2.85 V.

| | D7-D5 | D4-D0 | |
|--------|----------|--------------------|-----------|
| Name | _ | LDO1_OUT | |
| Access | — | R/W | |
| Data | Reserved | LDO1 Output volta | ge (V) |
| | D7-D5 | 5'h00 | 1.0 |
| | | 5'h01 | 1.1 |
| | | 5'h02 | 1.2 |
| | | 5'h03 | 1.3 |
| | | 5'h04 | 1.4 |
| | | 5'h05 | 1.5 |
| | | 5'h06 | 1.6 |
| | | 5'h07 | 1.7 |
| | | 5'h08 | 1.8 |
| | | 5'h09 | 1.9 |
| | | 5'h0A | 2.0 |
| | | 5'h0B | 2.1 |
| | | 5'h0C | 2.2 |
| | | 5'h0D | 2.3 |
| | | 5'h0E | 2.4 |
| | | 5'h0F | 2.5 |
| | | 5'h10 | 2.6 |
| | | 5'h11 | 2.7 |
| | | 5'h12 | 2.8 |
| | | 5'h13 | 2.9 |
| | | 5'h14 | 3.0 |
| | | 5'h15 | 3.1 |
| | | 5'h16 | 3.2 |
| | | 5'h17 | 3.3 |
| | | 5'h18 | 3.4 |
| | | 5'h19 | 3.5 |
| | | 5'h1A–5'h1F | 3.5 |
| Reset | 000 | Factory-Programmed | l Default |



8.6.1.15 LDO2 Control Register (LDO2VCR) – 0x3A

This register allows the user to program the output target voltage of LDO 2.

For "JJ11" voltage options LDO2 has a fixed output voltage of 2.85 V.

| | D7-D5 | D4-D0 | | | | |
|--------|----------|-------------------------|------------------|--|--|--|
| Name | _ | LC | 002_OUT | | | |
| Access | — | | R/W | | | |
| Data | Reserved | LDO2 Output voltage (V) | | | | |
| | | 5'h00 | 1.0 | | | |
| | | 5'h01 | 1.1 | | | |
| | | 5'h02 | 1.2 | | | |
| | | 5'h03 | 1.3 | | | |
| | | 5'h04 | 1.4 | | | |
| | | 5'h05 | 1.5 | | | |
| | | 5'h06 | 1.6 | | | |
| | | 5'h07 | 1.7 | | | |
| | | 5'h08 | 1.8 | | | |
| | | 5'h09 | 1.9 | | | |
| | | 5'h0A | 2.0 | | | |
| | | 5'h0B | 2.1 | | | |
| | | 5'h0C | 2.2 | | | |
| | | 5'h0D | 2.3 | | | |
| | | 5'h0E | 2.4 | | | |
| | | 5'h0F | 2.5 | | | |
| | | 5'h10 | 2.6 | | | |
| | | 5'h11 | 2.7 | | | |
| | | 5'h12 | 2.8 | | | |
| | | 5'h13 | 2.9 | | | |
| | | 5'h14 | 3.0 | | | |
| | | 5'h15 | 3.1 | | | |
| | | 5'h16 | 3.2 | | | |
| | | 5'h17 | 3.3 | | | |
| | | 5'h18 | 3.4 | | | |
| | | 5'h19 | 3.5 | | | |
| | | 5'h1A–5'h1F | 3.5 | | | |
| Reset | 000 | Factory-Pro | ogrammed Default | | | |

9 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

9.1 Application Information

The LP3907 provides three control methods to turn ON/OFF four power rails:

- 1. EN_T Control: Provides pre-defined power up/down sequence. (Note: V_{IN}/Battery voltage must be settled approximately 8 ms, minimum, before EN_T be asserted high).
- 2. Individual GPIO/EN pin control: four EN pins provide max control flexibility without I²C.
- 3. I²C control: besides simple ON/OFF control, also provides access to all the user programmable registers.

See Register Maps for details.

9.2 Typical Application



Copyright © 2016, Texas Instruments Incorporated

Figure 45. LP3907 Typical Application

9.2.1 Design Requirements

Ten ceramic capacitors and two inductors are required for this application. These three external components must be selected very carefully for property operation. See *Detailed Design Procedure*.

Typical Application (continued)

9.2.2 Detailed Design Procedure

9.2.2.1 Custom Design With WEBENCH® Tools

Click here to create a custom design using the LP3907 device with the WEBENCH® Power Designer.

- 1. Start by entering the input voltage (V_{IN}), output voltage (V_{OUT}), and output current (I_{OUT}) requirements.
- 2. Optimize the design for key parameters such as efficiency, footprint, and cost using the optimizer dial.
- 3. Compare the generated design with other possible solutions from Texas Instruments.

The WEBENCH Power Designer provides a customized schematic along with a list of materials with real-time pricing and component availability.

In most cases, these actions are available:

- Run electrical simulations to see important waveforms and circuit performance
- Run thermal simulations to understand board thermal performance
- Export customized schematic and layout into popular CAD formats
- Print PDF reports for the design, and share the design with colleagues

Get more information about WEBENCH tools at www.ti.com/WEBENCH.

9.2.2.2 Component Selection

9.2.2.2.1 Inductors for SW1 And SW2

There are two main considerations when choosing an inductor; the inductor must not saturate and the inductor current ripple is small enough to achieve the desired output voltage ripple. Care must be taken when reviewing the different saturation current ratings that are specified by different manufacturers. Saturation current ratings are typically specified at 25°C, so ratings at maximum ambient temperature of the application must be requested from the manufacturer.

There are two methods to choose the inductor saturation current rating:

9.2.2.2.1.1 Method 1:

The saturation current is greater than the sum of the maximum load current and the worst case average-to-peak inductor current. This can be written as follows:

 $I_{\text{sat}} > I_{\text{outmax}} + I_{\text{ripple}}$

where $I_{\text{ripple}} = \left(\frac{1}{f}\right) x \left(\frac{V_{\text{IN}} - V_{\text{OUT}}}{2L}\right) x \left(\frac{V_{\text{OUT}}}{V_{\text{IN}}}\right)$

where

- I_{RIPPLE} = Maximum load current
- I_{OUTMAX} = Average to peak inductor current
- V_{IN} = Maximum input voltage to the buck
- L = Min inductor value including worse case tolerances (30% drop can be considered for method 1)
- f = Minimum switching frequency (1.6 MHz)
- V_{OUT} = Buck output voltage

9.2.2.2.1.2 Method 2:

A more conservative and recommended approach is to choose an inductor that has saturation current rating greater than the maximum current limit of 1250 mA for Buck1 and 1750 mA for Buck2.

Given a peak-to-peak current ripple (IPP) the inductor needs to be at least

$$L \ge \left(\frac{V_{\text{IN}} \cdot V_{\text{OUT}}}{I_{\text{PP}}}\right) X \left(\frac{V_{\text{OUT}}}{V_{\text{IN}}}\right) X \left(\frac{1}{f}\right)$$

(7)

(6)

Typical Application (continued)

| INDUCTOR | VALUE (µH) | DESCRIPTION | NOTES |
|---------------------|------------|----------------|------------|
| L _{SW} 1,2 | 2.2 | SW1,2 inductor | DCR: 70 mΩ |

9.2.2.2.2 External Capacitors

The regulators on the LP3907 require external capacitors for regulator stability. These are specifically designed for portable applications requiring minimum board space and smallest components. These capacitors must be correctly selected for good performance.

9.2.2.3 LDO Capacitor Selection

9.2.2.3.1 Input Capacitor

An input capacitor is required for stability. It is recommended that a $1-\mu F$ capacitor be connected between the LDO input pin and ground (this capacitance value may be increased without limit).

This capacitor must be located a distance of not more than 1 cm from the input pin and returned to a clean analog ground. Any good quality ceramic, tantalum, or film capacitor may be used at the input.

Important: Tantalum capacitors can suffer catastrophic failures due to surge currents when connected to a low impedance source of power (such as a battery or a very large capacitor). If a tantalum capacitor is used at the input, it must be ensured by the manufacturer to have a surge current rating sufficient for the application.

There are no requirements for the equivalent series resistance (ESR) on the input capacitor, but tolerance and temperature coefficient must be considered when selecting the capacitor to ensure the capacitance remains approximately 1 μ F over the entire operating temperature range.

9.2.2.3.2 Output Capacitor

The LDOs on the LP3907 are designed specifically to work with very small ceramic output capacitors. A 0.47- μ F ceramic capacitor (temperature types Z5U, Y5V or X7R) with ESR between 5 m Ω to 500 m Ω , is suitable in the application circuit.

It is also possible to use tantalum or film capacitors at the device output, C_{OUT} (or V_{OUT}), but these are not as attractive for reasons of size and cost.

The output capacitor must meet the requirement for the minimum value of capacitance and also have an ESR value that is within the range 5 m Ω to 500 m Ω for stability.

9.2.2.3.3 Capacitor Characteristics

The LDOs are designed to work with ceramic capacitors on the output to take advantage of the benefits they offer. For capacitance values in the range of 0.47 μ F to 4.7 μ F, ceramic capacitors are the smallest, least expensive and have the lowest ESR values, thus making them best for eliminating high frequency noise. The ESR of a typical 1- μ F ceramic capacitor is in the range of 20 m Ω to 40 m Ω , which easily meets the ESR requirement for stability for the LDOs.

For both input and output capacitors, careful interpretation of the capacitor specification is required to ensure correct device operation. The capacitor value can change greatly, depending on the operating conditions and capacitor type.

In particular, the output capacitor selection should take account of all the capacitor parameters, to ensure that the specification is met within the application. The capacitance can vary with DC bias conditions as well as temperature and frequency of operation. Capacitor values will also show some decrease over time due to aging. The capacitor parameters are also dependent on the particular case size, with smaller sizes giving poorer performance figures in general. As an example, Figure 46 is a typical graph comparing different capacitor case sizes.





Figure 46. Graph Showing Typical Variation in Capacitance vs. DC Bias

As shown in the graph, increasing the DC Bias condition can result in the capacitance value that falls below the minimum value given in the recommended capacitor specifications table. Note that the graph shows the capacitance out of spec for the 0402 case size capacitor at higher bias voltages. It is therefore recommended that the capacitor manufacturers' specifications for the nominal value capacitor are consulted for all conditions, as some capacitor sizes (for example, 0402) may not be suitable in the actual application.

The ceramic capacitor's capacitance can vary with temperature. The capacitor type X7R, which operates over a temperature range of -55° C to 125° C, only varies the capacitance to within ±15%. The capacitor type X5R has a similar tolerance over a reduced temperature range of -55° C to 85° C. Many large value ceramic capacitors, larger than 1 µF are manufactured with Z5U or Y5V temperature characteristics. Their capacitance can drop by more than 50% as the temperature varies from 25°C to 85° C. Therefore, X7R is recommended over Z5U and Y5V in applications where the ambient temperature changes significantly above or below 25°C.

Tantalum capacitors are less desirable than ceramic for use as output capacitors because they are more expensive when comparing equivalent capacitance and voltage ratings in the 0.47-µF to 4.7-µF range.

Another important consideration is that tantalum capacitors have higher ESR values than equivalent size ceramics. This means that while it may be possible to find a tantalum capacitor with an ESR value within the stable range, it would have to be larger in capacitance (which means bigger and more costly) than a ceramic capacitor with the same ESR value. Note, also, that the ESR of a typical tantalum increases about 2:1 as the temperature goes from 25° C down to -40° C, so some guard band must be allowed.

9.2.2.3.4 Input Capacitor Selection for SW1 And SW2

A ceramic input capacitor of 10 μ F, 6.3 V is sufficient for the magnetic DC-DC converters. Place the input capacitor as close to the input of the device as possible. A large value may be used for improved input voltage filtering. The recommended capacitor types are X7R or X5R. Y5V type capacitors should not be used. DC bias characteristics of ceramic capacitors must be considered when selecting case sizes like 0805 and 0603. The input filter capacitor supplies current to the PFET switch of the DC-DC converter in the first half of each cycle and reduces voltage ripple imposed on the input power source. A ceramic capacitor's low ESR provides the best noise filtering of the input voltage spikes due to fast current transients. A capacitor with sufficient ripple current rating must be selected. The Input current ripple can be calculated as:

$$I_{rms} = I_{outmax} \sqrt{\frac{V_{OUT}}{V_{IN}} \left(1 + \frac{r^2}{12}\right)} \text{ where } r = \frac{(V_{in} - V_{out}) \times V_{out}}{L \times f \times I_{outmax} \times V_{in}}$$
(8)

The worse case is when $V_{IN} = 2 V_{OUT}$.

9.2.2.3.5 Output Capacitor Selection for SW1, SW2

A 10-µF, 6.3-V ceramic capacitor must be used on the output of the SW1 and SW2 magnetic DC-DC converters. The output capacitor must be mounted as close to the output of the device as possible. A large value may be used for improved input voltage filtering. The recommended capacitor types are X7R or X5R. Y5V type capacitors should not be used. DC bias characteristics of ceramic capacitors must be considered when selecting case sizes like 0805 and 0603. DC bias characteristics vary from manufacturer to manufacturer, and DC bias curves should be requested from them and analyzed as part of the capacitor selection process.

The output filter capacitor of the magnetic DC-DC converter smooths out current flow from the inductor to the load, helps maintain a steady output voltage during transient load changes and reduces output voltage ripple. These capacitors must be selected with sufficient capacitance and sufficiently low ESD to perform these functions.

The output voltage ripple is caused by the charging and discharging of the output capacitor and also due to its ESR and can be calculated as follows:

$$V_{pp-c} = \frac{I_{ripple}}{4 x f x C}$$
(9)

Voltage peak-to-peak ripple due to ESR can be expressed as follows:

 $V_{PP-ESR} = 2 \times I_{RIPPLE} \times R_{ESR}$

Because the V_{PP-C} and V_{PP-ESR} are out of phase, the rms value can be used to get an approximate value of the peak-to-peak ripple:

$$V_{pp-rms} = \sqrt{V_{pp-c}^2 + V_{pp-esr}^2}$$
(11)

Note that the output voltage ripple is dependent on the inductor current ripple and the equivalent series resistance of the output capacitor (R_{ESR}). The R_{ESR} is frequency dependent as well as temperature dependent. Calculate the R_{ESR} with the applicable switching frequency and ambient temperature.

| CAPACITOR | MIN VALUE (µF) | DESCRIPTION | RECOMMENDED TYPE |
|-------------------|----------------|-----------------------|---------------------|
| C _{LDO1} | 0.47 | LDO1 output capacitor | Ceramic, 6.3 V, X5R |
| C _{LDO2} | 0.47 | LDO2 output capacitor | Ceramic, 6.3 V, X5R |
| C _{SW1} | 10 | SW1 output capacitor | Ceramic, 6.3 V, X5R |
| C _{SW2} | 10 | SW2 output capacitor | Ceramic, 6.3 V, X5R |

Table 9. Suggested Capacitor Values

9.2.2.3.6 I²C Pullup Resistor

Both SDA and SCL pins must have pullup resistors connected to VINLDO12 or to the power supply of the I²C master. The values of the pullup resistors (typical approximately 1.8 kΩ) are determined by the capacitance of the bus. A resistor that is too large, combined with a given bus capacitance, results in a rise time that would violate the maximum rise time specification. A too-small resistor results in a contention with the pulldown transistor on either slave(s) or master.

9.2.2.4 Operation Without I²C Interface

Operation of the LP3907 without the I²C interface is possible if the system can operate with default values for the LDO and Buck regulators (see Factory Programmable Options.) The I²C-less system must rely on the correct default output values of the LDO and Buck converters.

9.2.2.4.1 High V_{IN} High-Load Operation

Additional information is provided when the IC is operated at extremes of V_{IN} and regulator loads. These are described in terms of the junction temperature and, buck output ripple management.



www.ti.com.cn

(11)

(10)



9.2.2.4.2 Junction Temperature

The maximum junction temperature $T_{J-MAX-OP}$ of 125°C of the device package Equation 12 through Equation 17 demonstrate junction temperature determination, ambient temperature T_{A-MAX} , and total chip power must be controlled to keep T_J below this maximum:

 $\mathbf{T}_{J-MAX-OP} = T_{A-MAX} + (R_{\theta JA}) [^{\circ}C/Watt] \times (P_{D-MAX}) [Watts]$

Total device power dissipation P_{D-MAX} is the sum of the individual power dissipation of the four regulators plus a minor amount for chip overhead. Chip overhead is Bias, TSD, and LDO analog.

| $P_{D-MAX} = P_{LD01} + P_{LD02} + P_{BUCK1} + P_{BUCK2} + (0.0001A \times V_{IN})$ [Watts]. | (13) |
|--|------|
|--|------|

Power dissipation of LDO1:

| | λ | A1 (44 |
|-----------------------------|---|--------|
| $P_{LDO1} = (V_{INLDO1} - $ | VOUTLDO1) × IOUTLDO1 [V × / | ጓ] (14 |

Power dissipation of LDO2:

 $P_{LDO2} = (V_{INLDO2} - V_{OUTLDO2}) \times I_{OUTLDO2} [V \times A]$

Power dissipation of Buck1:

 $P_{Buck1} = P_{IN} - P_{OUT} = V_{OUTBuck1} \times I_{OUTBuck1} \times (1 - \eta_1) / \eta_1 [V \times A]$

where

• $\eta_1 = \text{efficiency of buck 1}$

Power dissipation of Buck2:

 $P_{Buck2} = P_{IN} - P_{OUT} = V_{OUTBuck2} \times I_{OUTBuck2} \times (1 - \eta_2) / \eta_2 [V \times A]$

where

• $\eta_2 = \text{efficiency of Buck2}$

where

• η is the efficiency for the specific condition taken from efficiency graphs.

9.2.3 Application Curves



(12)

(15)

(16)

(17)



10 Power Supply Recommendations

If the EN_T is used to power up the device instead individual ENs , then VIN must be stable for approximately 8 ms minimum before EN_T be asserted high to ensure internal bias, reference, and the Flexible POR timing are stabilized. This initial EN_T delay is necessary only upon first time device power on for power sequencing function to operate properly.

10.1 Analog Power Signal Routing

All power inputs must be tied to the main VDD source (for example, battery), unless the user wishes to power it from another source. (that is, external LDO output).

The analog VDD inputs power the internal bias and error amplifiers, so they must be tied to the main VDD. The analog VDD inputs must have an input voltage between 2.8 V and 5.5 V, as specified in the *Recommended Operating Conditions (Bucks)* table earlier in the data sheet.

The other VINs (VINLDO1, VINLDO2) can have inputs lower than 2.8 V, as long as the input it higher than the programmed output (0.3 V).

The analog and digital grounds must be tied together outside of the chip to reduce noise coupling.



11 Layout

11.1 DSBGA Layout Guidelines

PC board layout is an important part of DC-DC converter design. Poor board layout can disrupt the performance of a DC-DC converter and surrounding circuitry by contributing to EMI, ground bounce, and resistive voltage loss in the traces. These can send erroneous signals to the DC-DC converter device, resulting in poor regulation or instability.

Good layout for the LP3907 device bucks can be implemented by following a few simple design rules below. Refer to Figure 49 for top-layer board buck layout.

- 1. Place the LP3907 bucks, inductor, and filter capacitors close together and make the traces short. The traces between these components carry relatively high switching currents and act as antennas. Following this rule reduces radiated noise. Special care must be given to place the input filter capacitor very close to the VIN and GND pin.
- 2. Arrange the components so that the switching current loops curl in the same direction. During the first half of each cycle, current flows from the input filter capacitor through the LP3907 bucks and inductor to the output filter capacitor and back through ground, forming a current loop. In the second half of each cycle, current is pulled up from ground through the LP3907 bucks by the inductor to the output filter capacitor and then back through ground forming a second current loop. Routing these loops so the current curls in the same direction prevents magnetic field reversal between the two half-cycles and reduces radiated noise.
- 3. Connect the ground pins of the LP3907 bucks and filter capacitors together using generous component-side copper fill as a pseudo-ground plane. Then, connect this to the ground-plane (if one is used) with several vias. This reduces ground-plane noise by preventing the switching currents from circulating through the ground plane. It also reduces ground bounce at the LP3907 bucks by giving it a low-impedance ground connection.
- 4. Use wide traces between the power components and for power connections to the DC-DC converter circuit. This reduces voltage errors caused by resistive losses across the traces.
- 5. Route noise sensitive traces, such as the voltage feedback path, away from noisy traces between the power components. The voltage feedback trace must remain close to the circuit of the LP3907 buck and must be direct but must be routed opposite to noisy components. This reduces EMI radiated onto the DC-DC converter's own voltage feedback trace. A good approach is to route the feedback trace on another layer and to have a ground plane between the top layer and layer on which the feedback trace is routed. In the same manner for the adjustable part it is desired to have the feedback dividers on the bottom layer.
- 6. Place noise sensitive circuitry, such as radio IF blocks, away from the DC-DC converter, CMOS digital blocks and other noisy circuitry. Interference with noise-sensitive circuitry in the system can be reduced through distance.

For more detailed layout specifications and information, refer to AN-1112 DSBGA Wafer Level Chip Scale Package.

LP3907 ZHCSEA3U – JUNE 2007 – REVISED JANUARY 2018 TEXAS INSTRUMENTS

www.ti.com.cn

11.2 Layout Example



Figure 49. LP3907 DSBGA Layout Example

11.3 Thermal Considerations of WQFN Package

The LP3907 is a monolithic device with integrated power FETs. For that reason, it is important to pay special attention to the thermal impedance of the WQFN package and to the PCB layout rules in order to maximize power dissipation of the WQFN package.

The WQFN package is designed for enhanced thermal performance and features an exposed die attach pad at the bottom center of the package that creates a direct path to the PCB for maximum power dissipation. Compared to the traditional leaded packages where the die attach pad is embedded inside the molding compound, the WQFN reduces one layer in the thermal path.

The thermal advantage of the WQFN package is fully realized only when the exposed die attach pad is soldered down to a thermal land on the PCB board with thermal vias planted underneath the thermal land. Based on thermal analysis of the WQFN package, the junction-to-ambient thermal resistance ($R_{\theta JA}$) can be improved by a factor of two when the die attach pad of the WQFN package is soldered directly onto the PCB with thermal land and thermal vias, as opposed to an alternative with no direct soldering to a thermal land. Typical pitch and outer diameter for thermal vias are 1.27 mm and 0.33 mm, respectively. Typical copper via barrel plating is 1 oz, although thicker copper may be used to further improve thermal performance. The LP3907 die attach pad is connected to the substrate of the device, and therefore, the thermal land and vias on the PCB board must be connected to ground (GND pin).

For more information on board layout techniques, refer to AN-1187 Leadless Lead Frame Package (LLP) on http://www.ti.com. This application note also discusses package handling, solder stencil, and the assembly process.



12 器件和文档支持

12.1 器件支持

12.1.1 开发支持

12.1.1.1 使用 WEBENCH® 工具创建定制设计

单击此处,使用 LP3907 器件并借助 WEBENCH® 电源设计器创建定制设计方案。

- 1. 首先键入输入电压 (V_{IN})、输出电压 (V_{OUT}) 和输出电流 (I_{OUT}) 要求。
- 2. 使用优化器拨盘优化关键参数设计,如效率、封装和成本。
- 3. 将生成的设计与德州仪器 (TI) 的其他解决方案进行比较。

WEBENCH 电源设计器可提供定制原理图以及罗列实时价格和组件供货情况的物料清单。

在多数情况下,可执行以下操作:

- 运行电气仿真,观察重要波形以及电路性能
- 运行热性能仿真,了解电路板热性能
- 将定制原理图和布局方案导出至常用 CAD 格式
- 打印设计方案的 PDF 报告并与同事共享

有关 WEBENCH 工具的详细信息,请访问 www.ti.com/WEBENCH。

12.2 文档支持

12.2.1 相关文档

请参阅如下相关文档:

- AN-1112 DSBGA 晶圆级芯片级封装
- 《AN-1187 无引线型引线框架封装 (LLP)》

12.3 商标

E2E is a trademark of Texas Instruments. WEBENCH is a registered trademark of Texas Instruments. All other trademarks are the property of their respective owners.

12.4 接收文档更新通知

如需接收文档更新通知,请导航至ti.com 上的器件产品文件夹。单击右上角的通知我进行注册,即可每周接收产品 信息更改摘要。有关更改的详细信息,请查看任何已修订文档中包含的修订历史记录。

12.5 社区资源

下列链接提供到 TI 社区资源的连接。链接的内容由各个分销商"按照原样"提供。这些内容并不构成 TI 技术规范, 并且不一定反映 TI 的观点;请参阅 TI 的 《使用条款》。

TI E2E™ 在线社区 TI 的工程师对工程师 (E2E) 社区。此社区的创建目的在于促进工程师之间的协作。在 e2e.ti.com 中,您可以咨询问题、分享知识、拓展思路并与同行工程师一道帮助解决问题。

设计支持 **71 参考设计支持** 可帮助您快速查找有帮助的 E2E 论坛、设计支持工具以及技术支持的联系信息。

12.6 静电放电警告

这些装置包含有限的内置 ESD 保护。存储或装卸时,应将导线一起截短或将装置放置于导电泡棉中,以防止 MOS 门极遭受静电损伤。

12.7 Glossary

SLYZ022 — TI Glossary.

This glossary lists and explains terms, acronyms, and definitions.

ZHCSEA3U – JUNE 2007 – REVISED JANUARY 2018



www.ti.com.cn

13 机械、封装和可订购信息

以下页面包含机械、封装和可订购信息。这些信息是指定器件的最新可用数据。数据如有变更, 恕不另行通知和修 订此文档。如欲获取此数据表的浏览器版本,请参阅左侧的导航。



10-Dec-2020

PACKAGING INFORMATION

| Orderable Device | Status | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead finish/ Ball material | MSL Peak Temp | Op Temp (°C) | Device Marking (4/5) | Samples |
|---------------------|--------|--------------|--------------------|------|----------------|-----------------|-------------------------------|--------------------|--------------|-------------------------|---------|
| | | | | | | | (6) | | | | |
| LP3907SQ-BJXQX/NOPB | ACTIVE | WQFN | RTW | 24 | 1000 | RoHS & Green | SN | Level-1-260C-UNLIM | -40 to 85 | 07BJXQX | Samples |
| LP3907SQ-JXQX/NOPB | ACTIVE | WQFN | RTW | 24 | 1000 | RoHS & Green | SN | Level-1-260C-UNLIM | -40 to 85 | 07-JXQX | Samples |
| LP3907SQ-PFX6W/NOPB | ACTIVE | WQFN | RTW | 24 | 1000 | RoHS & Green | SN | Level-1-260C-UNLIM | -40 to 85 | 7PFX6W | Samples |
| LP3907SQ-PJXIX/NOPB | ACTIVE | WQFN | RTW | 24 | 1000 | RoHS & Green | SN | Level-1-260C-UNLIM | -40 to 85 | 07PJXIX | Samples |
| LP3907SQ-TJXIP/NOPB | ACTIVE | WQFN | RTW | 24 | 1000 | RoHS & Green | SN | Level-1-260C-UNLIM | -40 to 85 | 07TJXIP | Samples |
| LP3907TL-JJ11/NOPB | ACTIVE | DSBGA | YZR | 25 | 250 | RoHS & Green | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | V013 | Samples |
| LP3907TL-JJCP/NOPB | ACTIVE | DSBGA | YZR | 25 | 250 | RoHS & Green | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | V016 | Samples |
| LP3907TL-JSXS/NOPB | ACTIVE | DSBGA | YZR | 25 | 250 | RoHS & Green | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | V012 | Samples |
| LP3907TL-PLNTO/NOPB | ACTIVE | DSBGA | YZR | 25 | 250 | RoHS & Green | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | V027 | Samples |
| LP3907TLX-JJ11/NOPB | ACTIVE | DSBGA | YZR | 25 | 3000 | RoHS & Green | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | V013 | Samples |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ RoHS: TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (CI) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

⁽³⁾ MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.



www.ti.com

PACKAGE OPTION ADDENDUM

10-Dec-2020

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

⁽⁶⁾ Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

www.ti.com

Texas Instruments

TAPE AND REEL INFORMATION





QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



| *All dimensions are nominal | | | | | | | | | | | | |
|-----------------------------|-----------------|--------------------|------|------|--------------------------|--------------------------|------------|------------|------------|------------|-----------|------------------|
| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
| LP3907SQ-BJXQX/NOPB | WQFN | RTW | 24 | 1000 | 178.0 | 12.4 | 4.3 | 4.3 | 1.3 | 8.0 | 12.0 | Q1 |
| LP3907SQ-JXQX/NOPB | WQFN | RTW | 24 | 1000 | 178.0 | 12.4 | 4.3 | 4.3 | 1.3 | 8.0 | 12.0 | Q1 |
| LP3907SQ-PFX6W/NOPB | WQFN | RTW | 24 | 1000 | 178.0 | 12.4 | 4.3 | 4.3 | 1.3 | 8.0 | 12.0 | Q1 |
| LP3907SQ-PJXIX/NOPB | WQFN | RTW | 24 | 1000 | 178.0 | 12.4 | 4.3 | 4.3 | 1.3 | 8.0 | 12.0 | Q1 |
| LP3907SQ-TJXIP/NOPB | WQFN | RTW | 24 | 1000 | 178.0 | 12.4 | 4.3 | 4.3 | 1.3 | 8.0 | 12.0 | Q1 |
| LP3907TL-JJ11/NOPB | DSBGA | YZR | 25 | 250 | 178.0 | 8.4 | 2.69 | 2.69 | 0.76 | 4.0 | 8.0 | Q1 |
| LP3907TL-JJCP/NOPB | DSBGA | YZR | 25 | 250 | 178.0 | 8.4 | 2.69 | 2.69 | 0.76 | 4.0 | 8.0 | Q1 |
| LP3907TL-JSXS/NOPB | DSBGA | YZR | 25 | 250 | 178.0 | 8.4 | 2.69 | 2.69 | 0.76 | 4.0 | 8.0 | Q1 |
| LP3907TL-PLNTO/NOPB | DSBGA | YZR | 25 | 250 | 178.0 | 8.4 | 2.69 | 2.69 | 0.76 | 4.0 | 8.0 | Q1 |
| LP3907TLX-JJ11/NOPB | DSBGA | YZR | 25 | 3000 | 178.0 | 8.4 | 2.69 | 2.69 | 0.76 | 4.0 | 8.0 | Q1 |

Texas Instruments

www.ti.com

PACKAGE MATERIALS INFORMATION

11-Jan-2018



| *All dimensions are nominal | | | | | | | |
|-----------------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
| LP3907SQ-BJXQX/NOPB | WQFN | RTW | 24 | 1000 | 210.0 | 185.0 | 35.0 |
| LP3907SQ-JXQX/NOPB | WQFN | RTW | 24 | 1000 | 210.0 | 185.0 | 35.0 |
| LP3907SQ-PFX6W/NOPB | WQFN | RTW | 24 | 1000 | 210.0 | 185.0 | 35.0 |
| LP3907SQ-PJXIX/NOPB | WQFN | RTW | 24 | 1000 | 210.0 | 185.0 | 35.0 |
| LP3907SQ-TJXIP/NOPB | WQFN | RTW | 24 | 1000 | 210.0 | 185.0 | 35.0 |
| LP3907TL-JJ11/NOPB | DSBGA | YZR | 25 | 250 | 210.0 | 185.0 | 35.0 |
| LP3907TL-JJCP/NOPB | DSBGA | YZR | 25 | 250 | 210.0 | 185.0 | 35.0 |
| LP3907TL-JSXS/NOPB | DSBGA | YZR | 25 | 250 | 210.0 | 185.0 | 35.0 |
| LP3907TL-PLNTO/NOPB | DSBGA | YZR | 25 | 250 | 210.0 | 185.0 | 35.0 |
| LP3907TLX-JJ11/NOPB | DSBGA | YZR | 25 | 3000 | 210.0 | 185.0 | 35.0 |

重要声明和免责声明

Ⅱ 均以"原样"提供技术性及可靠性数据(包括数据表)、设计资源(包括参考设计)、应用或其他设计建议、网络工具、安全信息和其他资源,不保证其中不含任何瑕疵,且不做任何明示或暗示的担保,包括但不限于对适销性、适合某特定用途或不侵犯任何第三方知识产权的暗示担保。

所述资源可供专业开发人员应用TI产品进行设计使用。您将对以下行为独自承担全部责任:(1)针对您的应用选择合适的TI产品;(2)设计、 验证并测试您的应用;(3)确保您的应用满足相应标准以及任何其他安全、安保或其他要求。所述资源如有变更,恕不另行通知。TI对您使用 所述资源的授权仅限于开发资源所涉及TI产品的相关应用。除此之外不得复制或展示所述资源,也不提供其它TI或任何第三方的知识产权授权 许可。如因使用所述资源而产生任何索赔、赔偿、成本、损失及债务等,TI对此概不负责,并且您须赔偿由此对TI及其代表造成的损害。

TI所提供产品均受TI的销售条款 (http://www.ti.com.cn/zh-cn/legal/termsofsale.html) 以及ti.com.cn上或随附TI产品提供的其他可适用条款的约束。TI提供所述资源并不扩展或以其他方式更改TI 针对TI 产品所发布的可适用的担保范围或担保免责声明。

邮寄地址:上海市浦东新区世纪大道 1568 号中建大厦 32 楼,邮政编码: 200122 Copyright © 2020 德州仪器半导体技术(上海)有限公司