

TPS7A7200-EP

ZHCSB45A – JUNE 2013 – REVISED JUNE 2013

2A,快速瞬态、低压降电压稳压器

查询样品: TPS7A7200-EP

特性

- 低压降: 2A 时为 180mV
- V_{输入}范围: 1.5V 至 6.5V
- 可配置固定 V_{输出}范围: 0.9V 至 3.5V 可调 V_{输出}范围: 0.9V 至 5.0V
- 极佳的负载和线路瞬态响应
- 与陶瓷输出电容器一起工作时保持稳定
- 1.5%线路、负载和温度上的精度
- 可编程软启动
- 电源正常 (PG) 输出
- 5mm × 5mm QFN-20 封装

应用范围

- 无线基础设施:串化解串器 (SerDes),现场可编程 栅极阵列 (FPGA), DSP™
- 射频 (RF) 组件: 压控振荡器 (VCO),数模转换器 (ADC),模数转换器 (DAC),低压差分信令 (LVDS)
- 机顶盒: 放大器, ADC, DAC, FPGA, DSP
- 无线局域网 (LAN), Bluetooth[®]
- 个人电脑 (PC) 和打印机
- 音频和视频

支持国防、航空航天、和医疗应用

- 受控基线
- 一个组装和测试场所
- 一个制造场所
- 扩展(-40°C 至 125°C)温度范围内可用
- 延长的产品生命周期
- 延长的产品变更通知
- 产品可追溯性



典型应用

说明

TPS7A7200低压降 (LDO) 稳压器设计用于追求极低压降功能的应用(2A 时为 180mV),此类应用的输入电压介于 1.5V 至 6.5V 之间。**TPS7A7200**提供一个介于 0.9V 至 3.5V 之间创新的、用户可配置的输入电压设置范围,从而 免除了对外部电阻器的需要并消除了任何与之相关的误差。

TPS7A7200具有极快的负载瞬态响应,与陶瓷输出电容器一起工作时保持稳定,并且在线路、负载、和温度上所支持的精度优于 **2%**。一个软启动引脚使得应用能够减少到负载的涌入电流。此外,一个开漏、电源正常信号可实现电源轨排序。

TPS77200采用一个 5mm × 5mm, 20 引脚 QFN 封装。



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

DSP is a trademark of Texas Instruments. Bluetooth is a registered trademark of Bluetooth SIG, Inc. All other trademarks are the property of their respective owners.



G311

ZHCSB45A - JUNE 2013 - REVISED JUNE 2013

www.ti.com.cn



Time (100µs/div)





ZHCSB45A - JUNE 2013 - REVISED JUNE 2013



www.ti.com.cn

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

	ORDERING INFORMATION ⁽¹⁾										
TJ	T _J PACKAGE ORDERABLE PART NUMBER TOP-SIDE MARKING VID NUMBER										
-40°C to 125°C	QFN (RGW)	TPS7A7200QRGWREP	SJK	V62/13612-01XE							

For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI
website at www.ti.com.

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Over operating free-air temperature range (unless otherwise noted).

		VALU	JE	
		MIN	MAX	UNIT
	IN, PG, EN	-0.3	+7.0	V
Voltage	SS, FB, SNS, OUT	-0.3	$V_{IN} + 0.3^{(2)}$	V
	50mV, 100mV, 200mV, 400mV, 800mV, 1.6V	-0.3	V _{OUT} + 0.3	V
Current	OUT	Internally	limited	А
Current	PG (sink current into IC)		5	mA
Tomporatura	Junction, T _J	-40	+150	*0
Temperature	Storage, T _{stg}	-40	+150	
Electrostatia Discharge Bating ⁽³⁾	Human body model (HBM, JESD22-A114A)		2	kV
Electrostatic Discharge Rating	Charged device model (CDM, JESD22-C101B.01)		500	V

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

2) The absolute maximum rating is V_{IN} + 0.3 V or +7.0 V, whichever is smaller.

(3) ESD testing is performed according to the respective JESD22 JEDEC standard.

THERMAL INFORMATION

		TPS7A7200-EP	
	THERMAL METRIC ⁽¹⁾	RGW	UNITS
		20 PINS	
θ _{JA}	Junction-to-ambient thermal resistance ⁽²⁾	35.7	
θ _{JCtop}	Junction-to-case (top) thermal resistance ⁽³⁾	33.6	
θ_{JB}	Junction-to-board thermal resistance ⁽⁴⁾	15.2	80 M
Ψ _{JT}	Junction-to-top characterization parameter ⁽⁵⁾	0.4	°C/W
Ψ_{JB}	Junction-to-board characterization parameter ⁽⁶⁾	15.4	
θ_{JCbot}	Junction-to-case (bottom) thermal resistance ⁽⁷⁾	3.8	

For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, SPRA953.
 The junction-to-ambient thermal resistance under natural convection is obtained in a simulation on a JEDEC-standard, high-K board, as specified in JESD51-7, in an environment described in JESD51-2a.

(3) The junction-to-case (top) thermal resistance is obtained by simulating a cold plate test on the package top. No specific JEDECstandard test exists, but a close description can be found in the ANSI SEMI standard G30-88.

(4) The junction-to-board thermal resistance is obtained by simulating in an environment with a ring cold plate fixture to control the PCB temperature, as described in JESD51-8.

(5) The junction-to-top characterization parameter, ψ_{JT} , estimates the junction temperature of a device in a real system and is extracted from the simulation data for obtaining θ_{JA} , using a procedure described in JESD51-2a (sections 6 and 7).

(6) The junction-to-board characterization parameter, ψ_{JB}, estimates the junction temperature of a device in a real system and is extracted from the simulation data for obtaining θ_{JA}, using a procedure described in JESD51-2a (sections 6 and 7).
 (7) The junction-to-case (bottom) thermal resistance is obtained by simulating a cold plate test on the exposed (power) pad. No specific

(7) The junction-to-case (bottom) thermal resistance is obtained by simulating a cold plate test on the exposed (power) pad. No specific JEDEC standard test exists, but a close description can be found in the ANSI SEMI standard G30-88.



ZHCSB45A – JUNE 2013 – REVISED JUNE 2013

ELECTRICAL CHARACTERISTICS

Over operating temperature range ($T_J = -40^{\circ}C$ to +125°C), 1.425 V $\leq V_{IN} \leq 6.5$ V, $V_{IN} \geq V_{OUT(TARGET)} + 0.3$ V or $V_{IN} \geq V_{OUT(TARGET)} + 0.5$ V⁽¹⁾⁽²⁾, OUT connected to 50 Ω to GND⁽³⁾, $V_{EN} = 1.1$ V, $C_{OUT} = 10 \ \mu$ F, $C_{SS} = 10 \ n$ F, $C_{FF} = 0 \ p$ F⁽⁴⁾, and PG pin pulled up to V_{IN} with 100 k Ω , 27 k $\Omega \leq R2 \leq 33$ k Ω for adjustable configuration⁽⁵⁾, unless otherwise noted. Typical values are at $T_J = +25^{\circ}C$.

	PARAMETER	TEST CONDITIONS	MIN	ТҮР	MAX	UNIT
V _{IN}	Input voltage range		1.425		6.5	V
V _(SS)	SS pin voltage			0.5		V
	Output voltage range	Adjustable with external feedback resistors	0.9		5.0	
		Fixed with voltage setting pins	0.9		3.5	V
VOUT	Output voltage accuracy ⁽⁶⁾⁽⁷⁾	Adjustable, 25 mA \leq I _{OUT} \leq 2 A	-2.0		+2.0	%
		Fixed, 25 mA \leq I _{OUT} \leq 2 A	-3.0		+3.0	
$\Delta V_{O(\Delta VI)}$	Line regulation	I _{OUT} = 25 mA		0.01		%/V
$\Delta V_{O(\Delta IO)}$	Load regulation	$25 \text{ mA} \le I_{\text{OUT}} \le 2 \text{ A}$		0.1		%/A
N/	Decement welter and (8)	$V_{OUT} \le 3.3 \text{ V}, I_{OUT} = 2 \text{ A}, V_{(FB)} = \text{GND}$			180	mV
V _(DO)	Dropout voltage	3.3 V < V _{OUT} , I _{OUT} = 2 A, V _(FB) = GND			470	mV
I _(LIM)	Output current limit	V_{OUT} forced at 0.9 × $V_{OUT(TARGET)},$ V_{IN} = 3.3 V, $V_{OUT(TARGET)}$ = 0.9 V	2.4	3.1		А
		Full load, I _{OUT} = 2 A		2.6		mA
I _(GND)	GND pin current	Minimum load, $V_{IN} = 6.5 \text{ V}, V_{OUT(TARGET)} = 0.9 \text{ V}, I_{OUT} = 25 \text{ mA}$			4	mA
		Shutdown, PG = (open), V _{IN} = 6.5 V, V _{OUT(TARGET)} = 0.9 V, V _(EN) < 0.5 V		0.1	5	μΑ
I _(EN)	EN pin current	$V_{IN} = 6.5 \text{ V}, V_{(EN)} = 0 \text{ V} \text{ and } 6.5 \text{ V}$			±0.1	μA
V _{IL(EN)}	EN pin low-level input voltage (disable device)		0		0.5	V
V _{IH(EN)}	EN pin high-level input voltage (enable device)		1.1		6.5	V
V _{IT(PG)}	PG pin threshold	For the direction PG \downarrow with decreasing V_{OUT}	0.85V _{OUT}	0.9V _{OUT}	0.96V _{OUT}	V
V _{hys(PG)}	PG pin hysteresis	For PG↑		$0.02V_{OUT}$		V
V _{OL(PG)}	PG pin low-level output voltage	$V_{OUT} < V_{IT(PG)}$, $I_{PG} = -1$ mA (current into device)			0.4	V
I _{lkg(PG)}	PG pin leakage current	$V_{OUT} > V_{IT(PG)}, V_{(PG)} = 6.5 V$			1	μA
I _(SS)	SS pin charging current	$V_{(SS)} = GND, V_{IN} = 3.3 V$	3.5	5.1	7.2	μA
V _n	Output noise voltage	BW = 100 Hz to 100 kHz, V _{IN} = 1.5 V, V _{OUT} = 1.2 V, I _{OUT} = 2 A		40.65		μV _{RMS}
-	Thermal objition temp time	Shutdown, temperature increasing		+160		°C
sd	mermai snutdown temperature	Reset, temperature decreasing		+140		°C
TJ	Operating junction temperature		-40		+125	°C

(1) When $V_{OUT} \le 3.5 \text{ V}$, $V_{IN} \ge (V_{OUT} + 0.3 \text{ V})$ or 1.425 V, whichever is greater; when $V_{OUT} > 3.5 \text{ V}$, $V_{IN} \ge (V_{OUT} + 0.5 \text{ V})$.

(2) V_{OUT(TARGET)} is the calculated target V_{OUT} value from the output voltage setting pins: 50mV, 100mV, 200mV, 400mV, 800mV, and 1.6V in fixed configuration, or the expected V_{OUT} value set by external feedback resistors in adjustable configuration.

(3) This 50- Ω load is disconnected when the test conditions specify an I_{QUT} value.

(4) C_{FF} is the capacitor between FB pin and OUT

(5) R2 is the bottom-side of the feedback resistor between the FB pin and OUT. See Figure 40 for details.

(6) When the TPS7A7200 is connected to external feedback resistors at the FB pin, external resistor tolerances are not included.

(7) The TPS7A7200 is not tested at $V_{OUT} = 0.9 V$, 2.7 $V \le V_{IN} \le 6.5 V$, and 500 mA $\le I_{OUT} \le 2 A$ because the power dissipation is higher than the maximum rating of the package. Also, this accuracy specification does not apply on any application condition that exceeds the power dissipation limit of the package.

(8) $V_{(DO)}$ is not defined for output voltage settings below 1.2 V.



ZHCSB45A - JUNE 2013-REVISED JUNE 2013

www.ti.com.cn



FUNCTIONAL BLOCK DIAGRAM

Figure 1. Functional Block Diagram

TEXAS INSTRUMENTS

ZHCSB45A-JUNE 2013-REVISED JUNE 2013

www.ti.com.cn

PIN CONFIGURATIONS



PIN DESCRIPTIONS

NAME	PIN	DESCRIPTION
50mV, 100mV, 200mV, 400mV, 800mV, 1.6V	5, 6, 7, 9, 10, 11	Output voltage setting pins. These pins should be connected to ground or left floating. Connecting these pins to ground increases the output voltage by the value of the pin name; multiple pins can be simultaneously connected to GND to select the desired output voltage. Leave these pins floating (open) when not in use. See the USER-CONFIGURABLE OUTPUT VOLTAGE section for more details.
EN	14	Enable pin. Driving this pin to logic high enables the device; driving the pin to logic low disables the device. See the <i>ENABLE AND SHUTDOWN THE DEVICE</i> section for more details.
FB	3	Output voltage feedback pin. Connected to the error amplifier. See the USER-CONFIGURABLE OUTPUT VOLTAGE and TRADITIONAL ADJUSTABLE CONFIGURATION sections for more details. A 220-pF ceramic capacitor from FB pin to OUT is highly recommended.
GND	8, 18	Ground pin.
IN	15, 16, 17	Unregulated supply voltage pin. It is recommended to connect an input capacitor to this pin. See INPUT CAPACITOR REQUIREMENTS for more details.
NC	12	Not internally connected. The NC pin is not connected to any electrical node. It is strongly recommended to connect this pin and the thermal pad to a large-area ground plane. See the <i>Power Dissipation</i> section for more details.
OUT	1, 19, 20	Regulated output pin. A 4.7-µF or larger capacitance is required for stability. See OUTPUT CAPACITOR REQUIREMENTS for more details.
PG	4	Active-high power good pin. An open-drain output that indicates when the output voltage reaches 90% of the target. See POWER GOOD for more details.
SNS	2	Output voltage sense input pin. See the USER-CONFIGURABLE OUTPUT VOLTAGE and TRADITIONAL ADJUSTABLE CONFIGURATION sections for more details.
SS	13	Soft-start pin. Leaving this pin open provides soft-start of the default setting. Connecting an external capacitor between this pin and the ground enables the soft-start function by forming an RC-delay circuit in combination with the integrated resistance on the silicon. See the <i>SOFT-START</i> section for more details.
Therm	al Pad	It is strongly recommended to connect the thermal pad to a large-area ground plane. If available, connect an electrically-floating, dedicated thermal plane to the thermal pad as well.



ZHCSB45A - JUNE 2013-REVISED JUNE 2013

www.ti.com.cn

TYPICAL CHARACTERISTICS

At $T_J = +25^{\circ}C$, $V_{IN} = V_{OUT(TARGET)} + 0.3 \text{ V}$, $I_{OUT} = 25 \text{ mA}$, $V_{(EN)} = V_{IN}$, $C_{IN} = 10 \ \mu\text{F}$, $C_{OUT} = 10 \ \mu\text{F}$, $C_{(SS)} = 10 \text{ nF}$, and the PG pin pulled up to V_{IN} with 100-k Ω pull-up resistor, unless otherwise noted.



EXAS NSTRUMENTS

www.ti.com.cn

ZHCSB45A-JUNE 2013-REVISED JUNE 2013



TYPICAL CHARACTERISTICS (continued)



TPS7A7200-EP

ZHCSB45A - JUNE 2013-REVISED JUNE 2013

www.ti.com.cn

TYPICAL CHARACTERISTICS (continued)

At $T_J = +25^{\circ}C$, $V_{IN} = V_{OUT(TARGET)} + 0.3$ V, $I_{OUT} = 25$ mA, $V_{(EN)} = V_{IN}$, $C_{IN} = 10$ µF, $C_{OUT} = 10$ µF, $C_{(SS)} = 10$ nF, and the PG pin pulled up to V_{IN} with 100-k Ω pull-up resistor, unless otherwise noted.





ZHCSB45A-JUNE 2013-REVISED JUNE 2013





TPS7A7200-EP

ZHCSB45A - JUNE 2013-REVISED JUNE 2013

www.ti.com.cn

TYPICAL CHARACTERISTICS (continued)

At $T_J = +25^{\circ}C$, $V_{IN} = V_{OUT(TARGET)} + 0.3$ V, $I_{OUT} = 25$ mA, $V_{(EN)} = V_{IN}$, $C_{IN} = 10$ µF, $C_{OUT} = 10$ µF, $C_{(SS)} = 10$ nF, and the PG pin pulled up to V_{IN} with 100-k Ω pull-up resistor, unless otherwise noted.



TEXAS INSTRUMENTS

www.ti.com.cn

ZHCSB45A-JUNE 2013-REVISED JUNE 2013





APPLICATION INFORMATION

OVERVIEW

The TPS7A7200 belongs to a family of new-generation LDO regulators that uses innovative circuitry to offer very-low dropout voltage along with the flexibility of a programmable output voltage.

The dropout voltage for this LDO regulator family is 0.18 V at 2 A. This voltage is ideal for making the TPS7A7200 into a point-of-load (POL) regulator because 0.18 V at 2 A is lower than any voltage gap among the most common voltage rails: 1.2 V, 1.5 V, 1.8 V, 2.5 V, 3.0 V, and 3.3 V. This device offers a fully user-configurable output voltage setting method. The TPS7A7200 output voltage can be programmed to any target value from 0.9 V to 3.5 V in 50-mV steps.

Another big advantage of using the TPS7A7200 is the wide range of available operating input voltages: from 1.5 V to 6.5 V. The TPS7A7200 also has very good line and load transient response. All these features allow the TPS7A7200 to meet most voltage-regulator needs for under-6-V applications, using only one device so that less time is spent on inventory control.

Texas Instruments also offers different output current ratings with other family devices: the TPS7A7100 (1 A) and TPS7A7300 (3 A).

USER-CONFIGURABLE OUTPUT VOLTAGE

Unlike traditional LDO devices, the TPS7A7200 comes with only one orderable part number; there is no adjustable or fixed output voltage option. The output voltage of the TPS7A7200 is selectable in accordance with the names given to the output voltage setting pins: 50mV, 100mV, 200mV, 400mV, 800mV, and 1.6V. For each pin connected to the ground, the output voltage setting increases by the value associated with that pin name, starting from the value of the reference voltage of 0.5 V; floating the pin(s) has no effect on the output voltage. Figure 34 through Figure 39 show examples of how to program the output voltages.





ZHCSB45A – JUNE 2013 – REVISED JUNE 2013











Figure 37. 2.5-V Configuration



Figure 39. 3.5-V Configuration



See Table 1 for a full list of target output voltages and corresponding pin settings. The voltage setting pins have a binary weight; therefore, the output voltage can be programmed to any value from 0.9 V to 3.5 V in 50-mV steps.

Figure 12 and Figure 13 shows this output voltage programming performance.

NOTE Any output voltage setting that is not listed in Table 1 is not covered in the Electrical Characteristics. For output voltages greater than 3.5 V, use a traditional adjustable configuration (see the TRADITIONAL ADJUSTABLE CONFIGURATION section).

V _{OUT(TARGET)} (V)	50mV	100mV	200mV	400mV	800mV	1.6V	V _{OUT(TARGET)} (V)	50mV	100mV	200mV	400mV	800mV	1.6V
0.90	open	open	open	GND	open	open	2.25	GND	GND	open	open	open	GND
0.95	GND	open	open	GND	open	open	2.30	open	open	GND	open	open	GND
1.00	open	GND	open	GND	open	open	2.35	GND	open	GND	open	open	GND
1.05	GND	GND	open	GND	open	open	2.40	open	GND	GND	open	open	GND
1.10	open	open	GND	GND	open	open	2.45	GND	GND	GND	open	open	GND
1.15	GND	open	GND	GND	open	open	2.50	open	open	open	GND	open	GND
1.20	open	GND	GND	GND	open	open	2.55	GND	open	open	GND	open	GND
1.25	GND	GND	GND	GND	open	open	2.60	open	GND	open	GND	open	GND
1.30	open	open	open	open	GND	open	2.65	GND	GND	open	GND	open	GND
1.35	GND	open	open	open	GND	open	2.70	open	open	GND	GND	open	GND
1.40	open	GND	open	open	GND	open	2.75	GND	open	GND	GND	open	GND
1.45	GND	GND	open	open	GND	open	2.80	open	GND	GND	GND	open	GND
1.50	open	open	GND	open	GND	open	2.85	GND	GND	GND	GND	open	GND
1.55	GND	open	GND	open	GND	open	2.90	open	open	open	open	GND	GND
1.60	open	GND	GND	open	GND	open	2.95	GND	open	open	open	GND	GND
1.65	GND	GND	GND	open	GND	open	3.00	open	GND	open	open	GND	GND
1.70	open	open	open	GND	GND	open	3.05	GND	GND	open	open	GND	GND
1.75	GND	open	open	GND	GND	open	3.10	open	open	GND	open	GND	GND
1.80	open	GND	open	GND	GND	open	3.15	GND	open	GND	open	GND	GND
1.85	GND	GND	open	GND	GND	open	3.20	open	GND	GND	open	GND	GND
1.90	open	open	GND	GND	GND	open	3.25	GND	GND	GND	open	GND	GND
1.95	GND	open	GND	GND	GND	open	3.30	open	open	open	GND	GND	GND
2.00	open	GND	GND	GND	GND	open	3.35	GND	open	open	GND	GND	GND
2.05	GND	GND	GND	GND	GND	open	3.40	open	GND	open	GND	GND	GND
2.10	open	open	open	open	open	GND	3.45	GND	GND	open	GND	GND	GND
2.15	GND	open	open	open	open	GND	3.50	open	open	GND	GND	GND	GND
2.20	open	GND	open	open	open	GND							

Table 1. User Configurable Output Voltage Setting

ZHCSB45A-JUNE 2013-REVISED JUNE 2013

TRADITIONAL ADJUSTABLE CONFIGURATION

For any output voltage target that is not supported in the USER-CONFIGURABLE OUTPUT VOLTAGE section, a traditional adjustable configuration with external-feedback resistors can be used with the TPS7A7200. Figure 40 shows how to configure the TPS7A7200 as an adjustable regulator with an equation and Table 2 lists recommended pairs of feedback resistor values.

NOTE

The bottom side of feedback resistor R2 in Figure 40 should be in the range of 27 k Ω to 33 k Ω in order to maintain the specified regulation accuracy.



Figure 40. Traditional Adjustable Configuration with External Resistors

	E96	SERIES	R40 \$	SERIES
(V)	R1 (kΩ)	R2 (kΩ)	R1 (kΩ)	R2 (kΩ)
1.00	30.1	30.1	30.0	30.0
1.20	39.2	28.0	43.7	31.5
1.50	61.9	30.9	60.0	30.0
1.80	80.6	30.9	80.0	30.7
1.90	86.6	30.9	87.5	31.5
2.50	115	28.7	112	28.0
3.00	147	29.4	150	30.0
3.30	165	29.4	175	31.5
5.00	280	30.9	243	27.2

Table 2. Recommended Feedback-Resistor Values



DROPOUT VOLTAGE

The TPS7A7200 maintains its output voltage regulation with a dropout voltage ($V_{IN} - V_{OUT}$) greater than 0.18 V under the test conditions specified in the Electrical Characteristics. In most power distribution tree (system) designs, the TPS7A7200 can be used with a 0.3-V difference in the common voltage rails (for example, from 3.3 V_{IN} to 3.0 V_{OUT}, from 1.8 V_{IN} to 1.5 V_{OUT}, or from 1.5 V_{IN} to 1.2 V_{IN}).

INPUT CAPACITOR REQUIREMENTS

As a result of its very fast transient response and low-dropout operation support, it is necessary to reduce the line impedance at the input pin of the TPS7A7200. The line impedance depends heavily on various factors, such as wire (PCB trace) resistance, wire inductance, and/or output impedance of the upstream voltage supply (power supply to the TPS7A7200). Therefore, a specific value for the input capacitance cannot be recommended until the previously listed factors are finalized.

In addition, simple usage of large input capacitance is known to form unwanted LC resonance in combination with input wire inductance. For example, a 5-nH inductor and a $10-\mu$ F input capacitor form an LC filter that has a resonance at 712 kHz. This value of 712 kHz is well inside the bandwidth of the TPS7A7200 control loop.

The best guideline is to use a capacitor of up to 1 μ F with well-designed wire connections (PCB layout) to the upstream supply. In case it is difficult to optimize the input line, use a large tantalum capacitor in combination with a good-quality, low-ESR, 1- μ F ceramic capacitor.

OUTPUT CAPACITOR REQUIREMENTS

The TPS7A7200 is designed to be stable with standard ceramic capacitors with capacitance values from 4.7 μ F to 47 μ F. The TPS7A7200 is evaluated using an X5R-type, 10- μ F ceramic capacitor. X5R- and X7R-type capacitors are highly recommended because they have minimal variation in value and ESR over temperature. Maximum ESR should be below 1.0 Ω .

As with any regulator, increasing the size of the output capacitor reduces overshoot and undershoot magnitude, but increases duration of the transient response.

UNDERVOLTAGE LOCK-OUT (UVLO)

The TPS7A7200 uses an undervoltage lock-out circuit to keep the output shut off until the internal circuitry is operating properly. The UVLO circuit has a deglitch feature that typically ignores undershoot of the input voltage upon the event of device start-up. Still, a poor input line impedance may cause a severe input voltage drop when the device powers on. As explained in the INPUT CAPACITOR REQUIREMENTS section, the input line impedance should be well-designed.

SOFT-START

The TPS7A7200 has a SS pin that provides a soft-start (slow start) function.

By leaving the SS pin open, the TPS7A7200 performes a soft-start by its default setting.

As shown in Figure 1, by connecting a capacitor between the SS pin and the ground, the C_{SS} capacitor forms an RC pair together with the integrated 50-k Ω resistor. The RC pair operates as an RC-delay circuit for the soft-start together with the internal 700-µs delay circuit.

The relationship between C_{SS} and the soft-start time is shown in Figure 31 through Figure 33.

CURRENT LIMIT

The TPS7A7200 internal current limit circuitry protects the regulator during fault conditions. During a current limit event, the output sources a fixed amount of current that is mostly independent of the output voltage. The current limit function is provided as a fail-safe mechanism and is not intended to be used regularly. Do not design any applications to use this current limit function as a part of expected normal operation. Extended periods of current limit operation degrade device reliability.

ZHCSB45A-JUNE 2013-REVISED JUNE 2013

ENABLE AND SHUTDOWN THE DEVICE

The EN pin switches the enable and disable (shutdown) states of the TPS7A7200. A logic high input at the EN pin enables the device; a logic low input disables the device. When disabled, the device consumption current is reduced.

POWER GOOD

The TPS7A7200 has a power good function that works with the PG output pin. When the output voltage undershoots the threshold voltage $V_{IT(PG)}$ during normal operation, the PG open-drain output turns from a high-impedance state to a low-impedance state. When the output voltage exceeds the $V_{IT(PG)}$ threshold by an amount greater than the PG hysteresis, $V_{hys(PG)}$, the PG open-drain output turns from a low-impedance state to high-impedance state. By connecting a pull-up resistor (usually between OUT and PG), any downstream device can receive an active-high enable logic signal.

When setting the output voltage to less than 1.8 V and using a pull-up resistor between OUT and PG, depending on the downstream device specifications, the downstream device may not accept the PG output as a valid highlevel logic voltage. In such cases, put a pull-up resistor between IN and PG, not between OUT and PG.

Figure 19 shows the open-drain output drive capability. The on-resistance of the open-drain transistor is calculated using Figure 19, and is approximately 200 Ω . Any pull-up resistor greater than 10 k Ω works fine for this purpose.

THERMAL INFORMATION

Thermal Protection

The thermal protection feature disables the output when the junction temperature rises to approximately +160°C, allowing the device to cool. When the junction temperature cools to approximately +140°C, the output circuitry is enabled. Depending on power dissipation, thermal resistance, and ambient temperature, the thermal protection circuit may cycle on and off. This thermal limit protects the device from damage as a result of overheating.

Any tendency to activate the thermal protection circuit indicates excessive power dissipation or an inadequate heatsink. For reliable operation, junction temperature should be limited to +125°C maximum. To estimate the margin of safety in a complete design (including heatsink), increase the ambient temperature until the thermal protection is triggered; use worst-case loads and signal conditions. For good reliability, thermal protection should trigger at least +35°C above the maximum expected ambient condition of your particular application. This configuration produces a worst-case junction temperature of +125°C at the highest expected ambient temperature and worst-case load.

The internal protection circuitry of the TPS7A7200 has been designed to protect against overload conditions. It was not intended to replace proper heatsinking. Continuously running the TPS7A7200 into thermal shutdown degrades device reliability.

Power Dissipation

Knowing the device power dissipation and proper sizing of the thermal plane that is connected to the tab or pad is critical to avoiding thermal shutdown and ensuring reliable operation.

Power dissipation of the device depends on input voltage and load conditions and can be calculated using Equation 1:

$$\mathsf{P}_{\mathsf{D}} = (\mathsf{V}_{\mathsf{IN}} - \mathsf{V}_{\mathsf{OUT}}) \times \mathsf{I}_{\mathsf{OUT}}$$

(1)

(2)

Power dissipation can be minimized and greater efficiency can be achieved by using the lowest possible input voltage necessary to achieve the required output voltage regulation.

On the QFN (RGW or RGT) package, the primary conduction path for heat is through the exposed pad to the PCB. The pad can be connected to ground or be left floating; however, it should be attached to an appropriate amount of copper PCB area to ensure the device does not overheat. The maximum junction-to-ambient thermal resistance depends on the maximum ambient temperature, maximum device junction temperature, and power dissipation of the device and can be calculated using Equation 2:

$$\mathsf{R}_{\theta \mathsf{J}\mathsf{A}} = \left(\frac{+125^{\circ}\mathsf{C} - \mathsf{T}_{\mathsf{A}}}{\mathsf{P}_{\mathsf{D}}}\right)$$



Knowing the maximum $R_{\theta JA}$, the minimum amount of PCB copper area needed for appropriate heatsinking can be estimated using Figure 41.



Figure 41. θ_{JA} vs Board Size

shows the variation of θ_{JA} as a function of ground plane copper area in the board. It is intended only as a guideline to demonstrate the effects of heat spreading in the ground plane and should not be used to estimate actual thermal performance in real application environments.

NOTE: When the device is mounted on an application PCB, it is strongly recommended to use Ψ_{JT} and Ψ_{JB} , as explained in the *Estimating Junction Temperature* section.

Estimating Junction Temperature

Using the thermal metrics Ψ_{JT} and Ψ_{JB} , as shown in the *Thermal Information* table, the junction temperature can be estimated with corresponding formulas (given in Equation 3). For backwards compatibility, an older θ_{JC} , *Top* parameter is listed as well.

$$\Psi_{\mathsf{JT}}: \quad \mathsf{T}_{\mathsf{J}} = \mathsf{T}_{\mathsf{T}} + \Psi_{\mathsf{JT}} \bullet \mathsf{P}_{\mathsf{D}}$$

$$\Psi_{JB}$$
: $T_J = T_B + \Psi_{JB} \bullet P_D$

Where:

 P_D is the power dissipation shown by Equation 2.

 T_T is the temperature at the center-top of the IC package.

 T_B is the PCB temperature measured 1mm away from the IC package *on the PCB surface* (see Figure 42). (3)

NOTE: Both T_T and T_B can be measured on actual application boards using a thermo-gun (an infrared thermometer).

For more information about measuring T_T and T_B , see Application Report SBVA025, Using New Thermal Metrics, available for download at www.ti.com.



ZHCSB45A-JUNE 2013-REVISED JUNE 2013

www.ti.com.cn



(a) Example RGW (QFN) Package Measurement

Figure 42. Measuring Points for T_T and T_B

By looking at Figure 43, the new thermal metrics (Ψ_{JT} and Ψ_{JB}) have very little dependency on board size. That is, using Ψ_{JT} or Ψ_{JB} with Equation 3 is a good way to estimate T_J by simply measuring T_T or T_B , regardless of the application board size.



Figure 43. Ψ_{JT} and Ψ_{JB} vs Board Size

For a more detailed discussion of why TI does not recommend using $\theta_{JC(top)}$ to determine thermal characteristics, refer to Application Report SBVA025, *Using New Thermal Metrics*, available for download at www.ti.com. For further information, refer to Application Report SPRA953, *IC Package Thermal Metrics*, also available on the TI website.



10-Dec-2020

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TPS7A7200QRGWREP	ACTIVE	VQFN	RGW	20	3000	RoHS & Green	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	SJK	Samples
V62/13612-01XE	ACTIVE	VQFN	RGW	20	3000	RoHS & Green	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	SJK	Samples

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ RoHS: TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (CI) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

⁽³⁾ MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

⁽⁵⁾ Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

⁽⁶⁾ Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



www.ti.com

PACKAGE OPTION ADDENDUM

10-Dec-2020

PACKAGE MATERIALS INFORMATION

www.ti.com

Texas Instruments

TAPE AND REEL INFORMATION





QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions	are nominal	

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS7A7200QRGWREP	VQFN	RGW	20	3000	330.0	12.4	5.3	5.3	1.1	8.0	12.0	Q2

TEXAS INSTRUMENTS

www.ti.com

PACKAGE MATERIALS INFORMATION

18-Aug-2014



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS7A7200QRGWREP	VQFN	RGW	20	3000	367.0	367.0	35.0

MECHANICAL DATA



A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5-1994.

- Β. This drawing is subject to change without notice.
- Quad Flat pack, No-leads (QFN) package configuration C.
- The package thermal pad must be soldered to the board for thermal and mechanical performance. D.
- E. See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.
- F. Falls within JEDEC MO-220.





THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.





RGW (S-PVQFN-N20)

PLASTIC QUAD FLATPACK NO-LEAD



NOTES: A. All linear dimensions are in millimeters.

B. This drawing is subject to change without notice.

- C. Publication IPC-7351 is recommended for alternate designs.
- D. This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, QFN Packages, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com http://www.ti.com.
- E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
- F. Customers should contact their board fabrication site for solder mask tolerances.



重要声明和免责声明

Ⅱ 均以"原样"提供技术性及可靠性数据(包括数据表)、设计资源(包括参考设计)、应用或其他设计建议、网络工具、安全信息和其他资源,不保证其中不含任何瑕疵,且不做任何明示或暗示的担保,包括但不限于对适销性、适合某特定用途或不侵犯任何第三方知识产权的暗示担保。

所述资源可供专业开发人员应用TI产品进行设计使用。您将对以下行为独自承担全部责任:(1)针对您的应用选择合适的TI产品;(2)设计、 验证并测试您的应用;(3)确保您的应用满足相应标准以及任何其他安全、安保或其他要求。所述资源如有变更,恕不另行通知。TI对您使用 所述资源的授权仅限于开发资源所涉及TI产品的相关应用。除此之外不得复制或展示所述资源,也不提供其它TI或任何第三方的知识产权授权 许可。如因使用所述资源而产生任何索赔、赔偿、成本、损失及债务等,TI对此概不负责,并且您须赔偿由此对TI及其代表造成的损害。

TI所提供产品均受TI的销售条款 (http://www.ti.com.cn/zh-cn/legal/termsofsale.html) 以及ti.com.cn上或随附TI产品提供的其他可适用条款的约束。TI提供所述资源并不扩展或以其他方式更改TI 针对TI 产品所发布的可适用的担保范围或担保免责声明。

邮寄地址:上海市浦东新区世纪大道 1568 号中建大厦 32 楼,邮政编码: 200122 Copyright © 2020 德州仪器半导体技术(上海)有限公司